

TSIM3

A generic SPARC architecture simulator capable of
emulating LEON-based computer systems

2020 User's Manual

The most important thing we build is trust

COBHAM
ADVANCED ELECTRONIC SOLUTIONS

TSIM3 Simulator User's Manual

Table of Contents

1. Introduction	6
1.1. General	6
1.2. Staged releasing	6
1.3. Supported host platforms and system requirements	6
1.4. Obtaining TSIM	6
1.5. License	7
1.6. Evaluation version	7
1.7. Problem reports	7
2. Installation	8
2.1. General	8
2.2. License key installation	8
3. Operation	10
3.1. Overview	10
3.2. Starting TSIM	10
3.3. Standalone mode commands	15
3.3.1. General commands	15
3.3.2. Time specification for commands	21
3.3.3. Tcl commands	21
3.3.4. Tcl variables	21
3.3.5. Core specific commands	21
3.4. Symbolic debug information	23
3.5. Breakpoints and watchpoints	23
3.6. Profiling	24
3.7. Performance	24
3.8. Code coverage	25
3.9. Check-pointing	26
3.10. Backtrace	26
3.11. Connecting to GDB	26
3.12. Thread support	28
3.12.1. TSIM thread commands	28
3.12.2. GDB thread commands	29
3.13. Synchronising TSIM time to external time	30
3.14. Debugging particular device types and devices	31
4. Emulation characteristics	32
4.1. Common behaviour	32
4.1.1. Timing	32
4.1.2. UARTs	32
4.1.3. Floating point unit (FPU)	33
4.1.4. Delayed write to special registers	33
4.1.5. Peripherals registers	33
4.1.6. Idle-loop optimisation	33
4.1.7. Chip-specific errata	33
4.2. LEON2 specific emulation	34
4.2.1. Processor	34
4.2.2. Cache memories	34
4.2.3. Interrupt controller	34
4.2.4. Power-down mode	34
4.2.5. Memory emulation	34
4.2.6. SPARC V8 MUL/DIV and V8E MAC instructions	34
4.2.7. FPU emulation	34
4.2.8. DSU and hardware breakpoints	34
4.3. LEON3 specific emulation	34
4.3.1. General	34
4.3.2. Processor	35
4.3.3. Cache memories	35

4.3.4. Power-down mode	35
4.3.5. Interrupt controller	35
4.3.6. Memory emulation	35
4.3.7. CASA instruction	35
4.3.8. SPARC V8 MUL/DIV and V8E MAC instructions	36
4.3.9. FPU emulation	36
4.3.10. DSU and hardware breakpoints	36
4.3.11. AHB status registers	36
4.3.12. GPTIMER emulation	36
4.3.13. GRTIMER emulation	36
4.4. LEON4 specific emulation	36
4.4.1. Processor	36
4.4.2. L1 Cache memories	36
4.4.3. L2 Cache memory	36
4.4.4. Power-down mode	37
4.4.5. Interrupt controller	37
4.4.6. Memory emulation	37
4.4.7. IOMMU	37
4.4.8. CASA instruction	37
4.4.9. SPARC V8 MUL/DIV and V8E MAC instructions	38
4.4.10. FPU emulation	38
4.4.11. DSU and hardware breakpoints	38
4.4.12. AHB status registers	38
4.4.13. GPTIMER emulation	38
5. Loadable modules	39
5.1. General module interface	39
5.1.1. Connecting specific modules	39
5.1.2. General module examples	40
5.2. TSIM exported emulation interfaces	40
5.2.1. simif structure	40
5.2.2. ioif structure	42
5.2.3. procif structure	42
5.3. LEON AHB emulation interface	43
5.3.1. Structure to be provided by AHB module	43
5.3.2. Big versus little endianness	46
5.3.3. AHB module example	46
5.3.4. AHB module limitations	47
5.4. I/O module interface	47
5.5. Adding startup options	47
5.6. Adding user commands	48
5.7. Loadable modules distributed with TSIM	48
6. TSIM library (TLIB)	50
7. Cobham Gaisler GR712RC emulation	51
7.1. Clock Gating Unit, CANMUX and GRGPREG	51
8. Cobham Gaisler GR716 emulation	52
8.1. GR716 Boot ROM	52
8.2. Dummy registers	53
8.3. DAC	53
9. Cobham Gaisler GR740 emulation	55
9.1. Dummy registers	55
10. Cobham UT699 emulation	56
11. Cobham UT699E emulation	57
12. Cobham UT700 emulation	58
13. Atmel AT697 emulation	59
14. GRCAN	60
14.1. Start up options	60
14.2. Commands	60
14.3. Debug flags	60

14.4. CAN interface	60
14.4.1. Connecting a user CAN model	60
14.4.2. CAN model API	61
14.4.3. Error injections	63
14.4.4. Commands	63
14.4.5. Debug status	63
14.4.6. Current limitations	63
15. CAN_OC interface	64
15.1. Start up options	64
15.2. Commands	64
15.3. Debug flags	64
15.4. Packet server	65
15.5. CAN packet server protocol	65
15.5.1. CAN message packet format	65
15.5.2. Error counter packet format	65
15.5.3. Acknowledge packet format	66
15.5.4. Acknowledge packet format	66
16. 10/100 Mbps Ethernet Media Access Controller interface	67
16.1. Start up options	67
16.2. Commands	67
16.3. Debug flags	67
16.4. Ethernet packet server	68
16.5. Ethernet packet server protocol	68
17. GPIO interface	69
17.1. Connecting a user GPIO model	69
17.2. GPIO model API	69
17.3. Commands	69
17.4. Debug flags	69
18. GRPCI, PCI initiator/target interface	71
18.1. Commands	71
18.2. Debug flags	71
18.3. PCI bus model API	71
18.3.1. PCI command table	72
18.4. Examples	73
19. GRSPW1, SpaceWire interface with RMAP support	74
19.1. Start up options	74
19.2. Commands	74
19.3. Debug flags	74
19.4. SpaceWire packet server	74
19.5. SpaceWire packet server protocol	75
19.5.1. Data packet format	75
19.5.2. Time code packet format	76
20. GRSPW2, SpaceWire interface with RMAP support	77
20.1. Start up options	77
20.2. Commands	77
20.3. Debug flags	78
20.4. SpaceWire packet server	78
20.5. SpaceWire packet server protocol	79
20.5.1. Flow control limitations	79
20.5.2. Data part packet format	79
20.5.3. Time code packet format	80
20.5.4. Link state packet format	81
20.5.5. Link control packet format	81
20.5.6. RX frequency packet format	82
20.5.7. Link error injection packet format	83
20.5.8. Packet error request packet format	84
20.6. Simple Mode	85
21. SPI interface	87

21.1. Connecting a user SPI model	87
21.2. SPI bus model API	87
21.3. Commands	87
21.4. Debug flags	87
22. SPIM interface	89
22.1. Connecting a user SPIM model to TSIM	89
22.2. SPIM model API	89
23. AT697 PCI interface	91
23.1. Commands	91
23.2. Debug flags	91
23.3. Registers	91
23.4. ESAPCI bus model API	92
23.4.1. PCI command table	93
23.5. Examples	94
24. TPS VxWorks 6.x AHB Module	95
24.1. Overview	95
24.2. Loading the module	95
24.3. Configuration	95
25. Support	96

1. Introduction

1.1. General

TSIM is a generic SPARC¹ architecture simulator capable of emulating LEON-based computer systems.

TSIM provides:

- Emulation of LEON2/3/4 processors in general and tailored emulation of specific chips
- High precision multi core CPU models with bus contention and inter-processor effects modelled on a per instruction level (LEON 3/4)
- FPU and MMU emulation
- Accelerated processor standby mode, allowing faster-than-realtime simulation speeds
- Standalone operation with scriptable Tcl command line
- Operation via remote connection from GNU debugger (GDB)
- Provided as a library to be included in larger simulator frameworks (to be released in a future update)
- 64-bit time for practically unlimited simulation periods
- Detailed instruction traces and AMBA bus traces
- Memory emulation, including SRAM, SDRAM, PROM, SPI memories, local data RAM and local instruction RAM.
- L2 cache emulation with support for configurable replacement, cache way locking, as well as and protected and uncached regions (currently only supported for LEON4)
- Emulation of interrupt controllers, UARTs, timers, IOMMU, SpaceWire interfaces, CAN controllers, SPI controllers, GPIOs, Ethernet interfaces, DAC, PCI
- Loadable modules to include user-defined device models
- Non-intrusive execution time profiling
- Non-intrusive code coverage monitoring
- Stack backtrace with symbolic information
- Check-pointing capability to save and restore complete simulator state (to be released in a future update)
- Unlimited number of breakpoints and watchpoints
- Predefined simulation models for GR740, GR712RC, GR716, UT699, UT700 and AT697

1.2. Staged releasing

Some general features that are not yet available in this release, will be released in upcoming updates. This includes saving and restoring simulator state, using TSIM as a library and various features of the LEON4 L2 cache such as AMBA split response. This is noted as such in the manual.

Additional simulation models for various I/O cores will be added in the future. Supported devices and interfaces of modelled chips are listed in their respective chapters. There, details on limitations of some of the models are also listed or pointed to.

Application program interfaces for user modules and user models are not yet finalised and thus subject to change. They are functional in their current form, unless otherwise noted, and usage examples are included in the distribution.

1.3. Supported host platforms and system requirements

TSIM supports the following host platforms: Linux and Windows 10.

1.4. Obtaining TSIM

The primary site for TSIM is the Cobham Gaisler website [<https://www.gaisler.com>] where the latest version of TSIM can be ordered and evaluation versions downloaded.

¹SPARC is a registered trademark of SPARC International

1.5. License

TSIM3 LEON2, TSIM3 LEON3 and TSIM3 LEON4 are licensed separately as separate products. Emulation of the GR716 LEON3FT microcontroller is available in TSIM3 LEON3, but can also be licensed separately as TSIM3 GR716 that simulates GR716 only.

The license text can be found in `license.txt` in the top directory after installation. Please contact sales@gaisler.com to acquire a license.

1.6. Evaluation version

An evaluation version of TSIM3 LEON3 is available from the Cobham Gaisler website [<https://www.gaisler.com>]. The evaluation version may only be used for evaluation and internal testing and only during a period of 21 days without purchasing a license. See the `license.txt` file that is included in the archive for details.

The evaluation version simulates a basic dual core LEON3 system, but can be made to simulate a single core system using the `-numcpus` option. The evaluation version is limited to 32-bit time. It does not support checkpointing, loadable modules, library interface, code coverage, configuration of caches, diagnostic cache accesses, configuration of memory or chip flags such as `-gr712rc` or `-ut700`. The `-help` option can show options that are available in the evaluation version. There are also upper limits on number of simulations restarts, instruction and bus trace lengths and number of frontend command executions.

1.7. Problem reports

Please send problem reports or comments to support@gaisler.com.

Customers with a valid support agreement may send questions to support@gaisler.com. Include a TSIM log when sending questions, please. A log can be obtained by starting TSIM with the command line switch `-log filename`. Try to include as much details as possible from commands such as **reg**, **inst/ahb** (enable history with **inst len len** or **ahb len len**), **bt** and with relevant debug options turned on. See also Chapter 25.

2. Installation

2.1. General

TSIM is distributed as a tar-file (e.g. tsim-leon3-3.0.1.tar.gz) with the following contents:

Table 2.1. TSIM content

Directory	Description
coverage	Source level coverage helper scripts
doc	TSIM documentation
examples/input	Example loadable modules for interfaces
examples/test	Example programs
examples/modules	Example loadable modules
license.txt	TSIM license text
share	Tcl distribution
tsim/linux-x64	TSIM binary for Linux
tsim/win64	TSIM binary for Windows

On Linux, the tar-file can be installed at any location with the following command:

```
tar xf tsim-leon3-3.0.1.tar.gz
```

On windows, the archive can be unpacked e.g. with the freely available 7-zip application.

TSIM must find the share directory to work properly. TSIM will try to automatically detect the location of the folder. If TSIM fails to automatically detect the folder, then the environment variable TSIM_SHARE can be set to point a moved share folder. If TSIM fails to find the share folder altogether it will fail to start up.

2.2. License key installation

TSIM is licensed using a Sentinel LDK USB hardware key and has support for node-locked and floating license keys. The type of key can be identified by the colour of the USB dongle. The node-locked keys are purple and the floating license keys are red.

1. Node-locked keys (purple USB key)

For node-locked keys, the Sentinel LDK Run-time for the key must be installed before the key can be used (see below).

2. Floating keys (red USB key)

In the case of floating keys, the Sentinel LDK Run-time must be installed on the server and the client computer (see below).

Sentinel LDK communicates via TCP and UDP on socket 1947. This socket is IANA-registered exclusively for this purpose. By default the client will find the server by issuing a UDP broadcast to local subnets on port 1947.

If broadcasting is not working or unwanted, then advanced network settings can be setup via the Sentinel Admin Control Center. The Sentinel Admin Control Center is accessed by opening the URL localhost:1947 in a web browser. The network settings are reached by selecting "Configuration" in the menu and then selecting the "Access to Remote License Managers" tab. Detailed information on how to setup the network settings can be found by selecting "Help" in the menu.

3. Sentinel LDK Runtime

The latest runtime can be found at the TSIM download page [<https://www.gaisler.com/index.php/downloads/simulators>]. Included in the downloaded Sentinel LDK runtime archive is a README file which contains detailed installation instructions.

Administrator privileges are required on Windows. On Linux it is required that the runtime is installed as root user.

3. Operation

3.1. Overview

TSIM can operate in three modes: standalone, used as a library and attached to GDB. In standalone mode, LEON applications can be loaded and simulated using a scriptable Tcl based command line interface. A number of commands are available to drive, investigate and interact with the simulation. When TSIM is used as a library, TSIM can be driven via a C API (see Chapter 6). This API makes standalone commands available as well as additional functionality. NOTE: The library mode is not yet available, but will be released in a future update. When attached to GDB, TSIM acts as a remote GDB target (see Section 3.11). Applications are loaded and debugged through GDB (or a GDB front-end such as DDD or Eclipse). In this mode it is also possible to use the standalone commands through the “monitor” GDB command.

3.2. Starting TSIM

TSIM is started as follows on a command line:

```
tsim-leon2 [options] [input_files]
tsim-leon3 [options] [input_files]
tsim-leon4 [options] [input_files]
```

Please note that when starting TSIM with a chip option, e.g. `-gr712rc` or `-gr716`, TSIM will configure chip specific features. This includes CPU configuration parameters like caches, MMU, FPU, as well as what interfaces are present and how they are configured. Thus, when using a chip option there is no need to manually configure parameters that affects configuration internal to the chosen chip. If a parameter is set by both a chip option and a option directly, TSIM will always use the direct option.

When using a TSIM3 GR716 license, the `-gr716` option is implicitly declared and thus GR716 features are already enabled. Some of the following options that are not supported by GR716 or is already enabled by the `-gr716` option have been disabled in the GR716 only release. This does not apply to `-gr716` when using a TSIM LEON3 license.

Many options can be used without an argument to enable or disable a feature but can also take an optional 1 or 0 as an argument. Many of these are documented as having the optional argument `[0 | 1]` without any description of the optional argument. For these cases, regardless of if the option enables or disables something a 1 argument is the same as no argument and will work as per the description of the option and a 0 argument will invert the meaning of the option. This can be used to override something enabled or disabled by earlier options.

Command line options can also be specified in the file `.tsimcfg` in the home directory. This file, if present, will be read at startup the contents will be prepended to the options given on the command line. In other words, options from the command line will, when possible, override options specified in the config file. See the `-cfg` option for how to turn this off or how to use a different file.

The following command line options are supported by TSIM:

```
-ahbstatus [ 0 | 1 ]
  Adds AHB status register support.
-asilallocate [ 0 | 1 ]
  Makes ASI 1 reads allocate cache lines (LEON3/4 only). This is enabled by default.
-at697e
  Set parameters according to the Atmel AT697E device (LEON2 only). See Chapter 13 for details on AT697
  emulation.
-banks <1 | 2 | 4>
  Sets how many RAM banks the SRAM is divided on. Supported values are 1, 2 or 4. Default is 1.
-bootstrap val
  Sets the GR716 bootstrap register to val (GR716 only).
-bopt [ 0 | 1 ]
  Enables idle-loop optimisation (see Section 4.1.6).
-bp [ 0 | 1 ]
  Enables emulation of LEON3/4 branch prediction
```

- bz [0|1]

Halt execution on all traps except privileged_instruction, fpu_disabled, window_overflow, window_underflow, asynchronous_interrupt and trap_instruction (As GRMON does when not using GRMON's -nb option). This halts at the pc and in the register window of the trapping instruction. Note that this does not function as an ordinary break in execution; continuing from this halt will re-execute the trapping instruction. This does not affect debugging through GDB. Use instead the -nb [0|1] option to set up that behaviour.
- c *file*

Evaluate the contents in the file *file* at startup. This is run through TSIM's Tcl interpreter and can thus contain Tcl code in general, including TSIM commands. This is a convenient way for specifying additional Tcl procedure definitions, for specifying simple sequences of TSIM commands as well as setting up more elaborate Tcl scripting of TSIM. See also the -e option on how to specify commands on the command line. Multiple -c and/or -e options can be given and will be evaluated in order.
- cfg *file*|none

Reads extra configuration options from *file*. If file name is "none" it will prevent a default configuration file .tsimcfg from the home directory from being read. Options from the command line will override options specified in the config file.
- cfgreg_and *and_mask*, -cfgreg_or *or_mask*

LEON2 only: Patch the Leon Configuration Register (0x80000024). The new value will be: (*reg* & *and_mask*)|*or_mask*.
- cas [0|1]

Enable emulation of the CASA instruction (LEON3/4 only).
- dcsiz *size*

Defines the set-size (KiB) of the LEON data cache. Allowed values are powers of two in the range 1 - 64 for LEON2 and 1-256 for LEON3/4. Default is 4 KiB.
- dlock [0|1]

Enable data cache line locking. Default is disabled.
- dlram *addr size*

Allocates *size* KiB of local data RAM (a.k.a. tightly coupled data memory and data scratch-pad RAM) at address *addr*. (LEON3/4)
- dlsiz <16|32>

Sets the line size of the LEON data cache (in bytes). Allowed values are 16 or 32. Default is 16.
- drepl <rnd|lru|lrr>

Sets the replacement algorithm for the LEON data cache. Allowed values are rnd (default for LEON2) for random replacement, lru (default for LEON3/4) for the least-recently-used replacement algorithm and lrr for the least-recently-replaced replacement algorithm.
- dsets *sets*

Defines the number of sets in the LEON data cache. Allowed values are 1 - 4.
- e *command(s)*

Executes *command(s)* at simulator startup. This is run through TSIM's Tcl interpreter and thus does not need to be a single command. For example, a string containing semicolon separated commands can be specified and will then run in sequence. See also the -c option on how to specify commands in a file. Multiple -e and/or -c options can be given and will be evaluated in order.
- eclipse [0|1]

Enable some special handling of the GDB protocol when connecting with Eclipse.
- ext *nr*

Enable extended IRQ in the interrupt controller with extended IRQ number *nr* (LEON3/4 only).
- fast_uart [0|1]

Run UARTs at infinite speed, rather than with correct baud rate.
- freq *system_clock*

Sets the simulated system clock in MHz. Default is 50.
- gdb [*port*]

Listen for GDB connection directly at start-up. If the port is not specified, the default port number 1234 is used. See also the -port option that changes the default GDB server port number without starting the server.

- gdbuartfwd [0|1]
Forward UART output to GDB when being connected over GDB. Which UART if any is forwarded is determined by the -u *X* option. The default behaviour is for GDB to not change UART forwarding behaviour.
- gr712rc
Set parameters to emulate the GR712RC device. See Chapter 7 for details on GR721RC emulation.
- gr716
Set parameters to emulate the GR716 device. See Chapter 8 for details on GR716 emulation.
- grfpu
Emulate the GRFPU floating point unit.
- grfpulite
Emulate the GRFPU-lite floating point unit (LEON3/4).
- help [*option*]
List short help on all available options or show specific help for a given option. Many options specific to certain cores will only be available when a chip option, that instantiates models that adds more options, is also given together with the -help option. Without an argument (i.e. it being the last option given), this displays short help for all available options. When the name of another option is given as an argument to -help, it will print, potentially more detailed, help about that option specifically.
- swbp [0|1]
Enable use of software breakpoints for GDB breakpoints. By default TSIM uses hardware breakpoints for GDB breakpoints. This does not affect standalone TSIM breakpoints.
- stack *addr*
Set initial stack pointer.
- icsize *size*
Defines the set-size (KiB) of the LEON instruction cache. Allowed values are powers of two in the range 1 - 64 for LEON2 and 1-256 for LEON3/4. Default is 4 KiB.
- ilock [0|1]
Enable instruction cache line locking. Default is disabled.
- ilram *addr size*
Allocates *size* KiB of local instruction RAM (a.k.a. tightly coupled instruction memory and instruction scratch-pad RAM) at address *addr*. (LEON3/4)
- ilsize <16|32>
Sets the line size of the LEON instruction cache (in bytes). Allowed values are 16 or 32. Default is 16 for LEON2/3 and 32 for LEON4.
- irepl <rnd|lru|lrr>
Sets the replacement algorithm for the LEON instruction cache. Allowed values are rnd (default for LEON2) for random replacement, lru (default for LEON3/4) for the least-recently-used replacement algorithm and lrr for the least-recently-replaced replacement algorithm.
- isets *sets*
Defines the number of sets in the LEON instruction cache. Allowed values are 1(default) - 4.
- log *filename*
Logs the console output to *filename*. If *filename* is preceded by '+' output is appended.
- mcfgX *value*
Set the reset value of memory configuration register *X*, where *X* can be 1, 2 or 3.
- mflat [0|1]
This switch should be used when the application software has been compiled with the gcc -mflat option, and debugging with GDB is done.
- mmu [0|1]
Enable MMU support. By default LEON2 and LEON3 does not have MMU support, and LEON4 has MMU support. Chip options, e.g. -gr712rc, enables MMU support when the corresponding chip has it.
- mod *file*
Loads an user specified loadable_module from *file*. The environment variable TSIM_MODULE_PATH can be set to a ':' separated (',' in WIN64) list of search paths.
- mul *value*
Set instruction cost of smul/umul to *value*.

- nb [0|1]
Do not break on error exceptions when debugging through GDB. To affect standalone TSIM or TLIB behaviour, see instead the -bz [0|1] option.
- nofpu [0|1]
Disables the FPU to emulate a system without FPU. Any floating-point instruction will generate an FP disabled trap.
- ni [0|1]
Prevents the GDB server from bootloader-like initialisation when using the **gdb reset** command and when starting the GDB server before any simulation has been done. No other commands are affected.
- mac [0|1]
Enable LEON MAC instructions.
- nosram [0|1]
Disable SRAM on startup. When SRAM is disabled, SDRAM will appear at 0x40000000.
- nothreads
Disable threads support.
- bmthreads
Force bare metal thread support, even when an OS is detected. Bare metal thread support consists of reporting each CPU as a thread to GDB. Bare metal thread support is default if no OS is detected.
- nov8 [0|1]
Disable SPARC V8 MUL/DIV instructions.
- nrtimers *val*
Adds support for more than 2 timers (in one timer unit). Value *val* can be in the range of 2 - 7 (LEON3/4 only). Default: 2. See also the -sametimerirq [0|1] and -timerirqbase *number* switches.
- numcpus *value*
Set number of CPUs between 1 and 4. In the LEON3 evaluation version, the maximum number of CPUs is limited to 2.
- nwinwin
Defines the number of register windows in the processor. Valid range is between 2 and 32. The default is 8. Only applicable to LEON3/4.
- port *port*
Set the port number *port* to be used for GDB communication. The default port number is 1234. The port number can also be specified with the -gdb option or the **gdb** command.
- pr [0|1]
Enable profiling automatically at startup.
- ram *ram_size*
Sets the amount of simulated RAM (KiB). Default is 4096.
- ramwidth <8|16|32>
By default, the RAM area at reset time is considered to be 32-bit. Specifying 8, 16 or 32 will initialise the memory width field in the memory configuration register to 8-, 16- or 32-bits. The only visible difference is in the instruction timing.
- rfpart [0|1]
Enable register window partitioning support.
- rom *rom_size*
Sets the amount of simulated ROM (KiB). Default is 2048.
- romwidth <8|16|32>
By default, the PROM area at reset time is considered to be 32-bit. Specifying 8, 16 or 32 will initialise the memory width field in the memory configuration register to 8-, 16- or 32-bits. The only visible difference is in the instruction timing.
- rtems *ver*
Override auto-detected RTEMS version for thread support. *ver* should be 46, 48, 48-edisoft or 410.
- sametimerirq [0|1]
Force the IRQ number to be the same for all timers (in one timer unit). Default: separate increasing IRQ numbers for each timer. (LEON3/4 only). See also the -nrtimers *val* and -timerirqbase *number* switches.
- sdfreq *frequency*
Set the frequency of the SDRAM in the SDCTRL in GR740. Default is 100 MHz.

- sdramwidth <32|64>
Set the SDRAM bus width of the SDCTRL in GR740 to 32 or 64 bit. Default is 64-bit. The only visible difference is in the instruction timing.
- sdram *sdram_size*
Sets the amount of simulated SDRAM (MiB). Default is 128.
- sdbanks <1|2>
Sets the number of SDRAM banks. Default is 1.
- strict_reset [0|1]
This enables strict reset behaviour for the memory controller. When this is not enabled, TSIM not only resets the memory controller configuration registers, but also sets up fields that are not reset in hardware. For example RAM banks sizes, RAM width are set up, and SDRAM is enabled if available and the RAM area is disabled if the `-nosram` option is used. This default behaviour is for convenience when working with RAM images. Enabling strict reset behaviour can be useful e.g. when testing boot loaders.
- sym *file*
Read symbols from *file*. This can be useful e.g. for self-extracting applications and applications that sets up non one-to-one MMU mapping.
- timer32 [0|1]
Use 32 bit timers instead of 24 bit. (LEON2 only)
- timerirqbase *number*
Set the IRQ number of the first timer (in one timer unit) to interrupt number *number* (LEON3/4 only). Default: 8. See also the `-nr timers_val` and `-same timer irq [0|1]` switches.
- u *X*
This options handles with which, if any, uart is to be connected to stdin/stdout. By default UART0 is connected stdin/stdout. Using this with *X* in the range 0 up to the number of UARTs (exclusive) sets up the chosen UART to be connected to stdin/stdout, whereas a negative *X* makes sure that none of the UARTs are connected to stdin/stdout. See also `-uartX device` for UARTs to other devices.
- uartX *device*

This option connects the chosen UART to a serial device. Here, *X* can be in the range 0 up to the number of UARTs (exclusive). See also `-u X` that is used to connect a UART to stdin/stdout.

On Linux, e.g. connecting the first uart to /dev/ttyUSB0 can be done with “-uart0 /dev/ttyUSB0”. On Linux, using the device /dev/ptmx will create a pseudo-terminal pair with the chosen uart at one end. TSIM prints out the name of the other end of the pair to be opened by host software communicating with the chosen uart.

On Windows use //./com1, //./com2 etc. to access the serial ports. The serial port settings can be adjusted by opening the relevant entry under “Ports (COM and LPT)” entry in the Device Manager and choosing the “Port Settings” tab in the dialogue that pops up.
- uart_fs <1|2|4|8|16|32>
Set UART FIFO depth in characters (LEON3/4 only). This setting affects all APBUARTs in the system. Valid configurations are 1 (default), 2, 4, 8, 16 and 32 characters. If the FIFO depth is configured to 1 the UART FIFO is not present instead only the holding register is present and FIFO level interrupts are not present. The FIFO interface is available for both fast and accurate mode, however the transmitter side in fast mode never fills the FIFO since characters are always sent immediately.
- upcounter [0|1]
Enables upcounter registers (ASR22/23). For LEON3/4 only.
- ut699
Set parameters to emulate the UT699 device. Note that when `-ut699` is given, snooping will be set as non-functional. This also sets up TSIM to simulate only one APBUART core. See Chapter 10 for details on UT699 emulation.
- ut699e
Set parameters to emulate the UT699E device. This also sets up TSIM to simulate only one APBUART core. See Chapter 11 for details on UT699E emulation.
- ut700
Set parameters to emulate the UT700 device. This also sets up TSIM to simulate only one APBUART core. See Chapter 12 for details on UT700 emulation.

- v
Turn on verbose output.
- vv
Turn on very verbose output.
- input_files*
Executable files to be loaded into memory. The input files are loaded into the emulated memory according to the entry point for each segment. Recognised formats are elf32, aout and srecords.

3.3. Standalone mode commands

The TSIM command line interface is a Tcl driven command line interface with a number of different type of recognised commands. There are general TSIM commands that are always present, native Tcl commands (see Section 3.3.3) that allows for Tcl scripting, as well as core specific commands that are available if specific devices are present in the simulated hardware configuration. See Section 3.3.1, Section 3.3.3 and Section 3.3.5 respectively. The **help** command can also be used to show a listing with short help for all commands, and to show more detailed help about specific commands.

As long as there are no ambiguities, short forms of the commands are allowed. For example, **dis**, is interpreted as **disassemble**, but **re** is reported as ambiguous. TSIM offers tab completion on things like commands names, subcommand names, symbols, device names and debug flags. In addition tab completion on Tcl variables are possible when after typing a “\$”.

Commands that takes an address as an argument can in general also take a symbol as an argument in place of an address, as well as tab complete on symbols. Some commands can take optional *cpuX* arguments to select a specific CPU, or for some commands a set of CPUs. For such arguments X is in this case replaced with the CPU id. In other words to select CPU 0, “cpu0” is used. Such *cpuX* arguments must be placed last in the command call. For commands that does something in the context of a specific CPU, the current CPU is the one that is affected. The **cpu** can be used to change which CPU that is the current CPU.

Typing a ‘Ctrl-C’ will interrupt a running simulator. Note however that in order to abort user created Tcl loops, the script should manually break out of the loop if the Tcl `tsim::interrupt` variable is not zero.

3.3.1. General commands

Below is a description of general commands

ahb [-f *file*] [*length*]

Display the latest *length* (default 30) entries in the AMBA bus trace history. Using -f *filename* will write the AMBA bus trace to file rather than print it.

Note: CPU accesses to local instruction RAM and local data RAM do not in general go via the AMBA bus and thus do not show up in the AMBA bus trace history. The one exception is instruction fetch from dual-port local *data* RAM on GR716.

ahb len *length*

Set the AMBA bus trace buffer length, clear the AMBA bus trace buffer and enable AMBA bus tracing. Setting it to zero clears and disables AMBA bus tracing.

batch *file* [*arguments...*]

Execute a Tcl script in the file *file*. During the script evaluation make *argv0* contain the script filename, *argv* contain a list of all the arguments that appear after the filename and *argc* will be the length of *argv*. See also the -c option on how to specify commands in a file that is evaluated at startup.

blload *file* [*startaddr*]

Load the binary file *file* into memory starting at *startaddr*. The default *startaddr* is the start of RAM memory. If an L2 cache is present, it will be flushed and invalidated and the loaded content will be placed uncached in the memory behind the L2 cache.

boot [*address/symbol* | -t] [*instructions* | *amount timeunit*]

Performs a cold boot. In other words, resets the simulator and starts simulation from time 0 bootloader-like initialisation. The event queue is emptied but memory contents and any set breakpoints remain. If an L2 cache is present, it is flushed, invalidated and disabled. If an address or symbol is given, execution starts

wmem, wmemh, wmemb *address value...*

Write a word, half-word or byte directly to simulated memory space. If several values are given, they are written to the consecutive word, half-word or byte addresses respectively.

xwmem *asi address value*

Write a word to simulated memory using ASI=*asi*.

3.3.2. Time specification for commands

Commands such as **run**, **boot**, **cont** and **go** supports simulating for a specified amount of time.

If an amount without a unit is specified, execution will stop after the specified number of instructions. If an amount and a time unit (with whitespace between) is specified, the execution will continue until the given time has passed (relative to the current time). The following time units are supported:

Table 3.1. Time units for commands that run simulation

Argument	Unit
c	cycles
us	microseconds
ms	milliseconds
s	seconds
min	minutes
h	hours
d	days

3.3.3. Tcl commands

TSIM has built-in support for Tcl 8.6. All command lines entered through the command line interface as well as via the GDB monitor command or executed from TLIB will pass through a Tcl-interpreter. This enables e.g. loops, variables, procedures, scripts, and arithmetic calculations for the user. Commands like **mem**, **reg**, **run**, **go**, **cont** and **step** gives useful Tcl return values that can be used for scripting.

Although this manual does not list all supported native Tcl commands, the TSIM **help tcl** can be used list short help for all supported native Tcl commands and **help cmdname** can be used to list full help for a given Tcl command. The help for the native Tcl **info** command can be listed with **help tclinfo**.

3.3.4. Tcl variables

TSIM provides TCL variables for commonly used values. Such as core registers and fields. The notation for registers are *coreX::register* and for fields *coreX::register::field*. This notation can be used to both read from a specific register and to set the value of it. Tab completion on these variables are supported.

3.3.5. Core specific commands

Many cores in the system has their own commands on the format *coreX_commandname*, where *X* is the index (starting from 0) off the core within the set of cores of the same type. For example **gpio0_status** shows the status of the first GPIO in the system. The availability of these commands depends upon what cores are present in the simulated system. The available cores in the simulated hardware can be shown with the **leon** command.

For some cores in the system there is a *coreX_status* command shows some additional status information. For some cores it is possible to enable extra debug information with their *coreX_dbg* command. This command takes a debug flag or a subcommand as argument. The flags are specific for each core type and explained in the respective chapter. Common for all *coreX_dbg* commands are the subcommands **all**, **clean** and **list** which will enable, disable or list all applicable debug flags respectively for the core in question.

gpioX_status

Print status for the GPIO core.

bootstrap_status

Prints the bootstrap register.

print_dummies

List all dummy register areas, if any. For some configurations TSIM implements registers of some cores as dummy registers. They can be read and written, but writes do not stick and reads will always yield 0.

3.4. Symbolic debug information

TSIM will automatically extract (.text) symbol information from elf-files. The symbols can be used where an address is expected:

```
tsim> bp main
breakpoint 1 at 0x310013b0: main + 0x4

tsim> dis strcmp 5

31004198 82120009 or      %o0, %o1, %g1      strcmp
3100419c 80886003 andcc   %g1, 0x3, %g0      strcmp + 0x4
310041a0 3280001e bne,a   0x31004218      strcmp + 0x8
310041a4 c24a0000 ldsb    [%o0], %g1      strcmp + 0xc
310041a8 c2024000 ld      [%o1], %g1      strcmp + 0x10
```

The **symbols list** command can be used to lookup and display all symbols. Symbols are automatically read from files loaded with the **load** command. To read in symbols from an alternate (elf) file use **symbols file**.

```
tsim> symbols dhrystone.elf
read 476 symbols
tsim> symbols lookup strcmp
Found address 0x31004198
tsim> symbols list
...
0x31000000 L __text_start
0x31000000 L __bcc_trap_table
0x31000000 L __bcc_entry_point
0x31001000 L __bcc_crt0
0x310010c8 L deregister_tm_clones
0x31001108 L register_tm_clones
0x3100115c L __do_global_dtors_aux
0x31001200 L call__do_global_dtors_aux
0x3100120c L frame_dummy
0x3100123c L call_frame_dummy
0x31001248 L Proc_1
0x310012f0 L Proc_2
0x31001324 L Proc_3
0x31001360 L Proc_4
0x31001394 L Proc_5
0x310013ac L main
0x31001868 L Proc_6
0x310018c4 L Proc_7
0x310018d8 L Proc_8
0x31001934 L Func_1
0x31001964 L Func_2
0x310019ac L Func_3
...
```

Reading symbols from alternate files is necessary when debugging applications where the image does not contain debugging symbols. This includes self-extracting applications and applications extracted by a bootrom, e.g. bootrom created with mkprom, application software images unpacked by the GR716 boot ROM and Linux images.

3.5. Breakpoints and watchpoints

TSIM supports execution breakpoints and write data watchpoints. In standalone mode, hardware breakpoints are always used and no instrumentation of memory or changes to memory are made. TSIM's hardware breakpoints are entirely handled outside the simulation model. No DSU hardware breakpoints are emulated. Breakpoints and watchpoints are set, displayed and deleted with the **bp** command.

When using the GDB interface, the GDB 'break' command requests TSIM to set breakpoints, which by default is handled using TSIM's internal hardware breakpoints. If **-swbp** is enabled, TSIM lets GDB handle software breakpoints by itself overwriting the breakpoint address with a 'ta l' instruction. In addition, hardware breakpoints can always

be inserted by using the GDB 'hbreak' command. Data write watchpoints are inserted using the 'watch' command. A watchpoint can only cover one word address, block watchpoints are currently not available.

3.6. Profiling

The profiling function calculates the amount of execution time spent in and under each subroutine of the simulated program. The profiling is non-intrusive. The Profiling does not have any affect on the execution in terms of simulated time and no changes needs to be done to the instrumented code. The profiling is made by periodically sample the execution point and the associated call tree. In other words, the profiling is inclusive. At each sample point all functions in the call stack are considered to be be executing, e.g. time spent in a function *g* called by a function *f* will tally up samples for both *f* and *g*. Cycles in the call graph are properly handled, as well as sections of the code where no stack is available (e.g. trap handlers).

The profiling information is printed as a list sorted on highest execution time ratio using **profile**. For a particular symbol, the presented percentage number is the percentage of all samples that the symbol was found in the call stack. By default all symbols with enough samples to reach 0.01% is printed. With a numeric argument the number of printed lines are limited to the given number of lines. By default, the profiling information for all CPUs that has been started during the sampling (including being started but in power down) are merged. With optional *cpuX* arguments, profiling can be shown for a subset of the available CPUs.

Profiling is enabled through the **profile enable** command. The sampling period is by default 1000 clocks which typically provides a good compromise between accuracy and performance. Other sampling periods can also be set through **profile enable n** where *n* is a the profile period in clock cycles. Profiling can be disabled through the **profile disable** command.

Below is an example profiling the Dhrystone benchmark:

```
tsim> load dhrystone.elf
...
tsim> profile enable
    Profiling enabled with sample period 1000
tsim> run
...
tsim> profile
    Merged profile for all started CPUs:

function          ratio(%)
-----
__bcc_crt0         99.99
main               99.79
Func_2             29.22
strcmp             25.64
memcpy             17.09
Proc_8              8.34
Func_1              4.77
Proc_7              4.37
Proc_6              1.78
tsim>
```

3.7. Performance

The **perf** command will display various execution statistics. A **perf reset** command will reset the statistics. This can be used if statistics shall be calculated only over a part of the program. Restarting simulation (e.g. via run, boot, or reset) also resets the statistic information.

By default, the performance information for all CPUs that has been started are merged. With optional *cpuX* arguments, performance can be shown for a subset of the available CPUs.

Below is an example of performance statistics

```
tsim> perf
    Performance statistics for CPU 0
    Cycles : 467054246
    Instructions : 334033114
    Overall CPI : 1.40
```

```

CPU performance (50.0 MHz) : 35.76 MOPS (35.76 MIPS, 0.00 MFLOPS)
Simulated time           : 9.34 s
Processor utilisation      : 100.00 %

Performance of the simulator:
Real-time performance     : 123.93 %
Simulator performance     : 44.32 MIPS
Used time (sys + user)    : 7.54 s
tsim>

```

3.8. Code coverage

To aid software verification, TSIM includes support for code coverage. When enabled, code coverage keeps a record for each 32-bit word in the emulated memory and monitors whether the location has been read, written or executed. Coverage information can be recorded individually per CPU or merged for all CPUs. Coverage information will be recorded also for cache hits. The coverage function is controlled by the coverage command:

coverage enable [merge percpu]	Enable coverage. Data will be merged for all CPUs if merge flag is specified, or recorded per CPU if percpu flag is specified. If no flag is specified then default is to merge. Note that changing coverage mode will reset the coverage data.
coverage disable	Disable coverage
coverage save [filename] [cpuX...]	Merge and write coverage data for specified CPUs to file (file name and CPU is optional). The coverage data will be merged for all CPUs if no CPU is specified.
coverage print address [len] [cpuX...]	Print coverage data to console, starting at address. If no CPU is specified the data will be merged for all CPUs. Else data for specified CPUs will be merged and printed.
coverage clear	Reset coverage data

The coverage data for each 32-bit word of memory consists of a 5-bit field, with bit0 (lsb) indicating that the word has been executed, bit1 indicating that the word has been written, and bit2 that the word has been read. Bit3 and bit4 indicates the presence of a branch instruction; if bit3 is set then the branch was taken while bit4 is set if the branch was not taken.

As an example, a coverage data of 0x6 would indicate that the word has been read and written, while 0x1 would indicate that the word has been executed. When the coverage data is printed to the console or save to a file, it is presented for one block of 32 words (128 bytes) per line:

```

tsim> cov print strcmp
31004198 : 1 1 11 0 1 1 1 11 0 1 1 1 1 1 1 1
310041d8 : 9 1 0 0 1 1 1 11 0 1 1 1 1 19 1 1
31004218 : 1 11 1 1 1 9 1 0 0 1 1 19 1 1 1 1
31004258 : 1 9 1 0 0 0 0 1 1 1 0 0 1 9 1 0
31004298 : 0 0 0 0 0 0 0 0 0 0 0 0 1 1 1 1
310042d8 : 1 1 1 1 9 1 0 0 0 0 0 0 0 0 0 0
31004318 : 0 0 0 0 1 1 19 1 1 1 0 0 0 0 0 0
31004358 : 0 0 0 0 0 0 0 0 0 0 4 0 0 0 0 0
31004398 : 0 0 4 0 0 0 0 0 0 0 0 0 0 0 0 0
310043d8 : 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
31004418 : 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
31004458 : 4 0 4 0 0 0 0 0 0 0 0 0 0 0 0 0
31004498 : 0 0 0 0 0 0 0 1 1 1 1 1 1 1 1 1
310044d8 : 1 11 1 1 1 11 1 1 1 11 0 1 1 1 11
31004518 : 1 1 1 11 0 1 1 1 19 1 1 1 1 1 1 1
31004558 : 11 1 1 1 19 1 1 11 0 1 1 1 1 1 1 1

```

When the code coverage is saved to file, only blocks with at least one coverage field set are written to the file. Block that have all the coverage fields set to zero are not saved in order to decrease the file size.

Only internally emulated memory are currently subject for code coverage. Any memory emulated in the user modules must be handled by a user-defined coverage function.

The memory controller address ranges that are monitored are based on the memory configuration at the moment when coverage is enabled. When using TSIM's startup parameters to configure memory, coverage can be enabled

before starting simulation. For instance, the range corresponding to SDRAM, for an FTMCTRL memory controller with the RAM area starting at 0x40000000, will begin at address 0x40000000 if TSIM was started with `-nosram` or `-ram 0`, or will begin at 0x60000000 otherwise. In case a bootloader or the application itself sets up the memory controller configuration, coverage should be enabled after this setup has been completed.

NOTE on MMU and coverage: The TSIM coverage system does not do any address translations. The monitored address ranges are based on the physical address ranges where TSIM emulates some kind of memory. There is currently no support for getting virtual address coverage for virtual addresses that untranslated would go outside these memory ranges.

When coverage is enabled, disassembly will include an extra column after the address, indicating the coverage data. This makes it easier to analyse which instructions has not been executed:

```
tstim> dis strcmp
31004198 1 82120009 or      %o0, %o1, %g1      strcmp
3100419c 1 80886003 andcc   %g1, 0x3, %g0      strcmp + 0x4
310041a0 11 3280001e bne,a   0x31004218      strcmp + 0x8
310041a4 0 c24a0000 ldsb    [%o0], %g1      strcmp + 0xc
310041a8 1 c2024000 ld      [%o1], %g1      strcmp + 0x10
310041ac 1 c4020000 ld      [%o0], %g2      strcmp + 0x14
310041b0 1 80a04002 cmp     %g1, %g2      strcmp + 0x18
310041b4 11 32800019 bne,a   0x31004218      strcmp + 0x1c
310041b8 0 c24a0000 ldsb    [%o0], %g1      strcmp + 0x20
310041bc 1 093fbfbf sethi   %hi(0xfefefc00), %g4      strcmp + 0x24
310041c0 1 07202020 sethi   %hi(0x80808000), %g3      strcmp + 0x28
310041c4 1 881122ff or      %g4, 0x2ff, %g4      strcmp + 0x2c
310041c8 1 8610e080 or      %g3, 0x80, %g3      strcmp + 0x30
310041cc 1 84004004 add     %g1, %g4, %g2      strcmp + 0x34
310041d0 1 82288001 andn    %g2, %g1, %g1      strcmp + 0x38
310041d4 1 80884003 andcc   %g1, %g3, %g0      strcmp + 0x3c
```

The coverage data is not saved or restored during check-pointing operations. When enabled, the coverage function reduces the simulation performance of about 30%. When disabled, the coverage function does not impact simulation performance.

Example scripts for annotating C code using saved coverage information from TSIM can be found in the coverage sub-directory.

3.9. Check-pointing

Saving and restoring simulator state is not yet available, but will be released in a future update.

TSIM can save and restore its complete state, allowing to resume simulation from a saved check-point. Saving the state is done with the `save file` command. The state is then saved to `file.tss`. To restore the state, use the `restore file` command.

NOTE: TSIM command line options are not stored. When restoring state in a different instance, TSIM should be started with the same options as when state was saved.

3.10. Backtrace

The `bt` command will display the current call backtrace and associated stack pointer:

```
tstim> bt
      %pc      %sp
#0  0x31004198  0x3000fcf8  strcmp + 0x0
#1  0x31001980  0x3000fcf8  Func_2 + 0x1c
#2  0x31001540  0x3000fd58  main + 0x194
#3  0x310010b0  0x3000fe10  __bcc_crt0 + 0xb0
```

3.11. Connecting to GDB

TSIM can act as a remote target for GDB, allowing symbolic debugging of target applications. GDB versions 6.8 and 8.2 are actively supported.

To initiate GDB communication, start the simulator with the `-gdb` switch or use the TSIM **gdb** command:

```
tsim> gdb
gdb interface: using port 1234
Starting GDB server. Use Ctrl-C to stop waiting for connection.
```

Then, start GDB in a different window and connect to TSIM using the extended-remote protocol:

```
$ sparc-rtems-gdb example.exe
(gdb) target extended-remote localhost:1234
Remote debugging using localhost:1234
0x0 in ?? ()
(gdb)
```

To interrupt simulation, Ctrl-C can be typed in both GDB and TSIM windows. The program can be restarted using the GDB **run** command but a **monitor gdb reset** and **load** has first to be executed in/via GDB to set up TSIM for a new run and reload the program image into the simulator. The **monitor gdb reset** command can be omitted if the MMU is not in use when using extended-remote target type and using the GDB **run** to start new simulation.

```
(gdb) monitor gdb reset
(gdb) load
Loading section .text, size 0x14e50 lma 0x40000000
Loading section .data, size 0x640 lma 0x40014e50
Start address 0x40000000 , load size 87184
Transfer rate: 697472 bits/sec, 278 bytes/write.
(gdb) run
```

The **monitor gdb reset** can always be omitted when using the extended-remote target type, with remote exec-file and starting each new execution via the GDB **run** command.

```
(gdb) target extended-remote :1234
Remote debugging using :1234
0x00000000 in ?? ()
(gdb) set remote exec-file /full/path/to/example.exe
(gdb) run
The program being debugged has been started already.
Start it from the beginning? (y or n) y
...

(gdb) run
The program being debugged has been started already.
Start it from the beginning? (y or n) y
...
```

When using remote target type (as opposed to extended-remote, e.g. when running via GDB in Eclipse) or not using run to start simulation, the **monitor gdb reset** should never be omitted before loading an image. In addition, when debugging multicore images in this situation, **monitor gdb postload** needs to be issued after loading to prepare all CPUs for a new run.

```
(gdb) target remote :1234
(gdb) monitor gdb reset
(gdb) load
Loading section .text, size 0x14e50 lma 0x40000000
Loading section .data, size 0x640 lma 0x40014e50
Start address 0x40000000 , load size 87184
Transfer rate: 697472 bits/sec, 278 bytes/write.
(gdb) monitor gdb postload
(gdb) cont
...
```

If GDB is detached using the **detach** command, the simulator returns to the command prompt, and the program can be debugged using the standard TSIM commands. The simulator can also be re-attached to GDB by issuing the **gdb** command to the simulator (and the **target** command to GDB). While attached, normal TSIM commands can be executed using the GDB **monitor** command. Output from the TSIM commands is then displayed in the GDB console. UART output forwarded to stdout is forwarded to GDB when running the simulation from GDB if TSIM is started with the `-gdbuartfwd` option.

TSIM translates SPARC traps into (Unix) signals which are communicated to GDB. If the application encounters a fatal trap, simulation will be stopped exactly on the failing instruction. The target memory and register values can then be examined in GDB to determine the error cause. To disable this and let execution continue through the corresponding trap handler instead, use the `-nb [0|1]` startup option.

Profiling an application executed from GDB is possible if the symbol table is loaded in TSIM before execution is started. GDB does not download the symbol information to TSIM, so the symbol table should be loaded using the monitor command:

```
(gdb) monitor symbols example.exe
read 158 symbols
```

When an application that has been compiled using the `gcc -mflat` option is debugged through GDB, TSIM should be started with `-mflat` in order to generate the correct stack frames to GDB.

3.12. Thread support

TSIM has thread support for the RTEMS 4.8 and RTEMS 4.10 operating system. Additional OS support will be added to future versions. The GDB interface of TSIM is also thread aware and the related GDB commands are described later.

3.12.1. TSIM thread commands

thread info - lists all known threads. The currently running thread is marked with an asterisk. (The wide example output below has been split into two parts.)

```
tsim> thread info
```

Name	Type	Id	Prio	Time (h:m:s)	Entry point	...
Int.	internal	0x09010001	255	5:30.682722	bsp_idle_thread	...
UI1	classic	0x0a010001	100	0.041217	system_init	...
ntwk	classic	0x0a010002	100	0.251199	soconnsleep	...
ETH0	classic	0x0a010003	100	0.000161	soconnsleep	...
* TA1	classic	0x0a010004	1	0.034739	prep_timer	...
TA2	classic	0x0a010005	1	0.025740	prep_timer	...
TA3	classic	0x0a010006	1	0.021357	prep_timer	...
TTCP	classic	0x0a010007	100	0.002914	rtems_ttcp_main	...

...	PC	State
...	0x40044bec _Thread_Dispatch + 0xd8	READY
...	0x40044bec _Thread_Dispatch + 0xd8	SUSP
...	0x40044bec _Thread_Dispatch + 0xd8	READY
...	0x40044bec _Thread_Dispatch + 0xd8	Wevnt
...	0x40006a28 printf + 0x4	READY
...	0x40044bec _Thread_Dispatch + 0xd8	DELAY
...	0x40044bec _Thread_Dispatch + 0xd8	DELAY
...	0x40044bec _Thread_Dispatch + 0xd8	Wevnt

thread bt *id* prints a backtrace of a thread.


```
#4 0x40029118 in accept (s=3, name=0x43feccf0, namelen=0x43feccec) at ../../../../../../rtems-4.6.5/cpukit/libnetworking/rtems/rtems_syscall.c:215
#5 0x40004028 in daemon () at ../../../../../../rtems-4.6.5/c/src/libnetworking/rtems_servers/ftpd.c:1925
#6 0x40053388 in _Thread_Handler () at ../../../../../../rtems-4.6.5/cpukit/score/src/threadhandler.c:123
#7 0x40053270 in __res_mkquery (op=0, dname=0x0, class=0, type=0, data=0x0, datalen=0, newrr_in=0x0, buf=0x0, buflen=0)
    at ../../../../../../rtems-4.6.5/cpukit/libnetworking/libc/res_mkquery.c:199
```

It is possible to use the **frame** command to select a stack frame of interest and examine the registers using the **info registers** command. Note that the **info registers** command only can see the following registers for an inactive task: g0-g7, i0-i7, o0-o7, pc and psr. The other registers will be displayed as 0:

```
(gdb) frame 5

#5 0x40004028 in daemon () at ../../../../../../rtems-4.6.5/c/src/libnetworking/rtems_servers/ftpd.c:1925
1925      ss = accept(s, (struct sockaddr *)&addr, &addrLen);

(gdb) info reg

g0          0x0      0
g1          0x0      0
g2          0xffffffff -1
g3          0x0      0
g4          0x0      0
g5          0x0      0
g6          0x0      0
g7          0x0      0
o0          0x3      3
o1          0x43feccf0 1140772080
o2          0x43feccec 1140772076
o3          0x0      0
o4          0xf34000e4 -213909276
o5          0x4007cc00 1074252800
sp          0x43fec888 0x43fec888
o7          0x40004020 1073758240
i0          0x4007ce88 1074253448
i1          0x4007ce88 1074253448
i2          0x400048fc 1073760508
i3          0x43feccf0 1140772080
i4          0x3      3
i5          0x1      1
i6          0x0      0
i7          0x0      0
i8          0x0      0
i9          0x0      0
i10         0x0      0
i11         0x40003f94 1073758100
i12         0x0      0
i13         0x43ffa8c8 1140830152
i14         0x0      0
i15         0x4007cd40 1074253120
fp          0x43fec8d8 0x43fec8d8
i17         0x40053380 1074082688
y           0x0      0
psr         0xf34000e0 -213909280
wim         0x0      0
tbr         0x0      0
pc          0x40004028 0x40004028 <daemon+148>
npc         0x4000402c 0x4000402c <daemon+152>
fsr         0x0      0
csr         0x0      0
```

It is not supported to set thread specific breakpoints. All breakpoints are global and stops the execution of all threads. It is not possible to change the value of registers other than those of the current thread.

3.13. Synchronising TSIM time to external time

To maximise simulation performance, TSIM executes as fast as possible doing no synchronisation of the simulation time with any external notion of time. This is especially apparent when the processor is in power-down mode and simulation time is increased by the events in the event queue alone.

To synchronise the simulation time with an external notion of time, events that handles synchronisation needs to be added to the event queue. The `walltimesync` example module in the `examples/modules` directory provides an example that makes sure that TSIM does not execute faster than real time. This example can be used as a template for synchronising to other notions of time. See Chapter 5 on how to use modules.

3.14. Debugging particular device types and devices

To enable printout of debug information one can issue the **dbgon** *flag* command on the TSIM3 command line to toggle the on/off state of a flag for all cores of a certain type. The debug flags that are available are described for each core in their chapters.

Many cores also have their own debug commands on the format *coreX_dbg* that targets single cores instead of all of one kind and that have support to set all or none of the debug flags options and list the current setting for the debug flags. See the sections on the respective cores for details.

4. Emulation characteristics

4.1. Common behaviour

4.1.1. Timing

The simulator time is maintained and incremented in terms of clock cycles. The parallel execution between the IU and FPU is modelled, as well as stalls due to operand dependencies. Instruction timing has been modelled after the real devices. Integer instructions have a higher accuracy than floating-point instructions due to the somewhat unpredictable operand-dependent timing of the FPU. Typical usage patterns have higher accuracy than atypical ones, e.g. having vs. not having caches enabled on LEON systems. Tracing using the **inst**, **ahb** or **hist** command will display the corresponding simulator time in the left column. This time indicates when the instruction or bus access finished. Cache misses, waitstates or data dependencies will delay the following fetch according to the incurred delay.

4.1.2. UARTs

The UART model can be operating in two modes, accurate mode and fast mode. In the accurate mode the baud rate and frame length is taken into account but in fast mode the UARTs operate at infinite speed. In fast mode the transmitter FIFO/holding register is always empty and a transmitter empty interrupt is generated directly after each write to the transmitter data register. The receivers can never overflow or generate errors. Fast mode is enabled with the `-fast_uart` switch.

Note that in accurate mode, it is possible that the last character of a program is not displayed on the console. This can happen if the program forces a processor in error mode, thereby terminating the simulation, before the last character has been shifted out from the transmitter shift register. To avoid this, an application can poll the UART status register and not force the processor in error mode before the transmitter shift registers are empty. The real hardware does not exhibit this problem since the UARTs continue to operate even when the processor is halted.

When an application is running with UART forwarded to the console (as the first UART is by default, or some other UART using the `-u` option) the following key sequences will be available. The sequences can be used to send key sequences to the UART that would otherwise be intercepted by the host operating system or to adjust the input to what the target system expects. For a key sequence to take effect, both key presses must be pressed within 1.5 seconds of each other. Otherwise, they will be forwarded as is.

Table 4.1. Uart control sequences

Key sequence	Action
Ctrl+A B	Toggle delete to backspace conversion
Ctrl+A C	Send break (Ctrl+C) to the running application
Ctrl+A D	Toggle backspace to delete conversion
Ctrl+A E	Toggle local echo on/off
Ctrl+A H	Show a help message
Ctrl+A N	Enable/disable newline insertion on carriage return
Ctrl+A S	Show current settings
Ctrl+A Z	Send suspend (Ctrl+Z) to the running application
Ctrl+A Ctrl+A	Send a single Ctrl+A to the running application

4.1.2.1. APBUART model (LEON3/4 only)

The APBUART model used on LEON3 and LEON4 systems has support for receiver and transmitter FIFO mode also. In this mode the additional FIFO flags and level interrupts are also modelled like the APBUART IP. FIFO mode is enabled by setting the FIFO depth to a larger value than 1 with the `-uart_fs` switch. FIFO mode is supported with both accurate and fast mode. However in fast mode the transmitter operates in infinite speed always causing the FIFO to be empty.

Loopback mode is supported both in fast and accurate mode. In fast mode transmitted characters directly ends up in the receiver. Similar to the hardware the CTSN/RTSN signals are connected together in loop back mode making flow control possible regardless of operating mode.

Flow control bit is supported but has a different effect compared to hardware when loopback mode is disabled. TSIM UARTs interfaces to user controlled devices (see `-uartX`) which may/may not implement flow control in different ways. When flow control is enabled APBUART receiver never overflows, however the transmitter operates independently of the flow control setting as if CTSN is always 0 by pausing the simulator until the character is transferred to the UART device.

The debugflag APBUART_ACC can be used with the TSIM command `uartX_dbg` to enable debug printouts each time a register access is made to the core. Here X is the index of the APBUART core.

4.1.2.2. UART model (LEON2 only)

The UART model of LEON2 automatically switch to fast mode when the scaler baud rate register is set to zero. This is different from the APBUART model where only the `-fast_uart` switch is used to determine the mode.

4.1.3. Floating point unit (FPU)

The models for the GRFPU-lite and GRFPU models supports parallel IU and FPU execution, deferred floating point traps and the floating point deferred trap queue. The model for the Meiko FPU on LEON2 models the FPU setup for AT697E and AT7913E with no parallel IU and FPU execution, no floating point queue and no deferred floating point traps.

The GRFPU model simulates all types calculation results and exceptions, including denormal numbers and NaN results. It does not however simulate the possibility of multiple outstanding floating point operations. The complex internal timing of the GRFPU is not modelled in detail.

The simulator implements (to some extent) data-dependent execution timing for the Meiko FPU and GRFPU-lite. The only discrepancy between TSIM and actual hardware in terms of results is that when NaN results are generated on Meiko FPU on LEON2 and GRFPU-lite, they can differ compared to real hardware in the significand bits (but not in the signalling/quiet bit).

4.1.4. Delayed write to special registers

The SPARC architecture defines that a write to the special registers (`%psr`, `%wim`, `%tbr`, `%fsr`, `%y`) may have up to 3 delay cycles, meaning that up to 3 of the instructions following a special register write might not 'see' the newly written value due to pipeline effects. While LEON have between 2 and 3 delay cycles, TSIM has 0. This does not affect simulation accuracy or timing as long as the SPARC ABI recommendations are followed that each special register write must always be followed by three NOP. If the three NOP are left out, the software might fail on real hardware while still executing 'correctly' on the simulator.

4.1.5. Peripherals registers

An overview of peripherals can be displayed with the `leon` command. Individual registers can be listed with the `info reg coreX` or `info reg addr` command.

4.1.6. Idle-loop optimisation

To minimise power consumption, LEON applications will typically place the processor in power-down mode when the idle task is scheduled in the operation system. In power-down mode, TSIM increments the event queue without executing any instructions, thereby significantly improving simulation performance. However, some (poorly written) code might use a busy loop (BA 0) instead of triggering power-down mode. The `-bopt` switch will enable a detection mechanism which will identify such behaviour and optimise the simulation as if the power-down mode was entered.

4.1.7. Chip-specific errata

Incorrect behaviour described in errata documents for specific devices are not emulated by TSIM in general.

4.2. LEON2 specific emulation

4.2.1. Processor

The LEON2 version of TSIM emulates the behaviour of the LEON2 VHDL model. The (optional) MMU can be emulated using the `-mmu` switch.

4.2.2. Cache memories

TSIM/LEON2 can emulate any permissible cache configuration using the `-icsize`, `-ilsize`, `-dcsiz` and `-dlsiz` options. Allowed sizes are 1 - 64 KiB with 16 - 32 bytes/line. The characteristics of the LEON multi-set caches can be emulated using the `-isets`, `-dsets`, `-irepl`, `-drelp`, `-ilock` and `-dlock` options. Diagnostic cache reads/writes are implemented. The simulator commands **icache** and **dcache** can be used to display cache contents. Starting TSIM with `-at697e` will configure that caches according to the Atmel AT697E device.

4.2.3. Interrupt controller

External interrupts are not implemented, so the I/O port interrupt register has no function. Internal interrupts are generated as defined in the LEON specification. All 15 interrupts can also be generated from the user defined I/O module using the `set_irq()` callback.

4.2.4. Power-down mode

The power-down register (0x80000018) is implemented as in the specification. In power-down mode, the simulator skips time until the next event in the event queue, thereby significantly increasing the simulation speed. A Ctrl-C in the simulator window will break execution, but will not make the CPU exit power-down mode.

4.2.5. Memory emulation

The memory configuration registers 1/2 are used to decode the simulated memory. The memory configuration registers has to be programmed by software to reflect the available memory, and the number and size of the memory banks. The waitstates fields must also be programmed with the correct configuration after reset. Both SRAM and functionally modelled SDRAM (with SRAM timing) can be emulated.

Using the `-banks` option, it is possible to set over how many RAM banks the external SRAM is divided in. For mkprom encapsulated programs, it is essential that the *same* RAM size and bank number setting is used for both mkprom and TSIM.

The memory EDAC of LEON2-FT is not implemented.

4.2.6. SPARC V8 MUL/DIV and V8E MAC instructions

TSIM/LEON2 by default supports the SPARC V8 multiply and divide instructions. To emulate LEON2 systems which do not implement these, use the `-nov8` option to disable multiply and divide instructions. TSIM/LEON2 optionally implements the SPARC V8E MAC instructions. To emulate LEON2 systems which implement these, use the `-mac` option to enable the MAC instructions, and make sure to not use `-nov8`.

4.2.7. FPU emulation

By default, TSIM/LEON2 emulates the Meiko FPU. The `-grfpu` command line option enables the GRFPU model. See Section 4.1.3 for details on the FPU models.

4.2.8. DSU and hardware breakpoints

The LEON debug support unit (DSU) and the hardware watchpoints (%asr24 - %asr31) are not emulated.

4.3. LEON3 specific emulation

4.3.1. General

The LEON3 version of TSIM by default emulates the behaviour of a generic LEON3. The system includes the following modules: LEON3 processor, APB bridge, IRQMP interrupt controller, FTMCTRL memory controller

(but EDAC is not modelled), GPTIMER timer units with 32-bit timers and APBUART UARTs. Chip options instead sets up TSIM to emulate a particular chip. Other hardware configuration options can change parameters from either the default values or from the values set up by a chip option.

4.3.2. Processor

The instruction timing of the emulated LEON3 processor is modelled after the LEON3 in GRLIB IP library and after the specific chips that have their own chip options. The processor can be configured with 2 - 32 register windows using the `-nwin` switch. The MMU can be emulated using the `-mmu` switch. Local instruction RAM and local data RAM can be added with the `-ilram` and `-dlram` switches.

4.3.3. Cache memories

TSIM can emulate any permissible cache configuration using the `-icsize`, `-ilsize`, `-dcsize` and `-dlsize` options. Allowed sizes are 1 - 256 KiB with 16 - 32 bytes/line. The characteristics of the LEON multi-way caches can be emulated using the `-isets`, `-dssets`, `-irepl`, `-drepl`, `-ilock` and `-dlock` options. Diagnostic cache reads/writes are implemented. The simulator commands **icache** and **dcache** can be used to display cache contents, flush caches and query cache status for given addresses.

The evaluation version of TSIM/LEON3 implements 2*4 KiB caches, with 16 bytes per line.

4.3.4. Power-down mode

The LEON3 power-down function is implemented as in the specification. When in power down mode, the simulator skips time until the next event in the event queue, thereby significantly increasing the simulation speed. A Ctrl-C in the simulator window will break execution, but will not make any CPU exit power-down mode.

4.3.5. Interrupt controller

The IRQMP interrupt controller model supports extended interrupts, multicore registers, interrupt maps, and interrupt timestamping. When having extended interrupts enabled, interrupts 1-31 can be generated. For GR716 interrupts 1-63 can be generated. Extended interrupts can be enabled by the `-ext` option, or with a chip option for a chip that has extended interrupts (e.g. `-gr712rc`, `-ut700` and `-ut699e`). Interrupts can be generated by user models using the `set_irq()` callback of TSIM's `ioif` struct. See Section 5.2.2 for details.

The debugflag `IRQMP_ACC` can be used with the TSIM command **irqmpX_dbg** to enable debug printouts each time a register access is made to the interrupt controller. Here X is the index of the interrupt controller.

4.3.6. Memory emulation

The FTMCTRL (without EDAC emulation) or the LEON2 memory controller is emulated in the LEON3 version of TSIM. The memory configuration registers 1 and 2 are used to decode the simulated memory. The memory configuration registers has to be programmed by software to reflect the available memory, and the number and size of the memory banks. Both SRAM and SDRAM can be emulated, however, the SDRAM model does not support sending commands using the SDRAM command field in `mcfg2`. The PROM area is basically modelled as MRAM.

The SRAM is configured using options like `-ram`, `-ramwidth`, `-banks` and `-nosram`. The SDRAM is configured using options like `-sdram` and `-sdbanks`. The PROM is configured using options like `-rom` and `-romwidth`.

When booting from PROM, it is important that the configuration done by the bootloader matches the system setup, just as for booting on actual hardware. TSIM however does not model any failure due to too few waitstates.

Options regarding memory characteristics are not available in the evaluation version of TSIM/LEON3.

4.3.7. CASA instruction

The `-cas` option or any chip option for a chip with CASA support enables emulation of the CASA instruction (LEON3/4 only). Using `-cas 0` can disable CASA support when otherwise already enabled.

4.3.8. SPARC V8 MUL/DIV and V8E MAC instructions

TSIM/LEON3 by default supports the SPARC V8 multiply and divide instructions. To emulate LEON3 systems which do not implement these, use the `-nov8` option to disable multiply and divide instructions. TSIM/LEON3 optionally implements the SPARC V8E MAC instructions. To emulate LEON3 systems which implement these, use the `-mac` option to enable the MAC instructions, and make sure to not use `-nov8`.

4.3.9. FPU emulation

By default, TSIM/LEON3 emulates the GRFPU-lite FPU unless a chip option for a chip with a GRFPU is used. The `-grfpu` command line option enables the GRFPU model. See Section 4.1.3 for details on the FPU models.

4.3.10. DSU and hardware breakpoints

The LEON debug support unit (DSU) and the hardware watchpoints (%asr24 - %asr31) are not emulated.

4.3.11. AHB status registers

When using `-ahbstatus` or a chip option for a chip that has AHB status registers, AHB status registers are enabled. As TSIM/LEON3 does not emulate FT, the CE bit will never be set by TSIM's internal memory models, but the `correctable_error()` function (Section 5.3.1) can be used in a user model to set it. Furthermore, the HMASTER field is set to the CPU index (starting at zero) when the CPU caused the error and one over the last CPU index (i.e. 1 in a one CPU system) when any other master caused the error.

4.3.12. GPTIMER emulation

The debugflag GPTIMER_ACC can be used with the TSIM command `gptimerX_dbg` to enable debug printouts each time a register access is made to the core. Here X is the index of the GPTIMER core.

4.3.13. GRTIMER emulation

When using `-gr712rc`, the GRTIMER core is modelled (in addition to the regular GPTIMER core).

The debugflag GRTIMER_ACC can be used with the TSIM command `grtimerX_dbg` to enable debug printouts each time a register access is made to the core. Here X is the index of the GRTIMER core.

4.4. LEON4 specific emulation

Currently, the only supported LEON4 configuration is GR740.

4.4.1. Processor

The four emulated LEON4 processors are modelled after the LEON4 VHDL model in GRLIB IP library and is configured to emulate GR740. Simulation of LEON4 in other configurations is not yet available.

4.4.2. L1 Cache memories

TSIM/LEON4 can emulate any permissible cache configuration using the `-icsize`, `-ilsize`, `-dcsize` and `-dlsize` options. Allowed sizes are 1 - 256 KiB with 16 - 32 bytes/line. The characteristics of the LEON multi-set caches can be emulated using the `-isets`, `-dsets`, `-irepl`, `-drepl`, `-ilock` and `-dlock` options. Diagnostic cache reads/writes are implemented. The simulator commands `icache` and `dcache` can be used to display cache contents, flush caches and query cache status for given addresses.

4.4.3. L2 Cache memory

GR740 has a 2 MiB L2 cache with 4 cache ways and 32 byte cache lines. The L2 cache has support for dynamically configurable replacement policies as well as locked ways. Individual memory regions can be write protected or marked uncacheable by the MTRR registers.

When starting TSIM the L2 cache is set up in reset state and thus disabled. The `run` command will as part of the boot-loading flush, invalidate and enable the L2 cache. The `boot` command will flush and invalidate the cache as part of restarting simulation but will otherwise leave it in its reset state. The L2 cache can otherwise be enabled or disabled via the register interface or the `l2cache enable` and `l2cache disable` commands.

The **l2cache** command shows the current overview of the state of the L2 cache. For more commands for flushing, invalidating the cache as well as investigating the L2 cache state, see the various **l2cache** subcommands in Section 3.3.1 or use the **help l2cache** command to list the available L2 cache commands.

4.4.3.1. Limitations of the L2 cache model

In this release, the L2 cache model has a number of features that are not yet supported. AMBA split responses and writethrough are not supported. In other words, only waitstate responses will be given and only copy-back will be performed. The different tuning settings available in the access control register are not modelled. Moreover, dirty cachelines are always modelled as fully dirty and not half dirty. These limitations have no functional effects on simulated software as long as the cache is flushed before disabling if the cache needs to be disabled.

No FT features are modelled. There is no EDAC emulation, error injection, scrubbing. This includes related registers and register fields, including the entire error status/control register. There is also no support for HPROT signals. These limitations are reflected in the registers shown by the **info reg** command for the L2 cache. Timing of cache clushing is not modelled.

Interacting with the L2 cache with commands such as the **mem** and **wmem** will affect the state the cache just as regular bus accesses would, including timing of future accesses when continuing (as opposed to restarting) execution. In the same way, **l2cache** commands that changes L2 cache state, will affect timing of future accesses when continuing execution.

4.4.4. Power-down mode

The LEON4 power-down function is implemented as in the specification. When in power down mode, the simulator skips time until the next event in the event queue, thereby significantly increasing the simulation speed. A Ctrl-C in the simulator window will break execution, but will not make any CPU exit power-down mode.

4.4.5. Interrupt controller

The IRQ(A)MP interrupt controller model supports multiple internal interrupt controllers, extended interrupts, multicore registers, interrupt maps, interrupt timestamping and extended interrupts. All 31 interrupts can be generated by user models using the `set_irq()` callback of TSIM's `ioif` struct. See Section 5.2.2 for details. The watchdog control and error mode status registers are not yet implemented.

The debugflag `IRQMP_ACC` can be used with the TSIM command **irqmpX_dbg** to enable debug printouts each time a register access is made to the interrupt controller. Here X is the index of the interrupt controller.

4.4.6. Memory emulation

The SDRAM controller behind the L2 cache is modelled for GR740. It can be configured with the `-sdram`, `-sdfreq` and `-sdbanks` options as well as through the SDRAM controller registers, `sdcfg1/sdcfg2`.

In this release the simulated timing is based on a CPU frequency of 250 or 50 MHz and a memory frequency of either 50 or 100 MHz, default memory frequency is 100 MHz. For CPU frequencies other than 250 or 50 MHz, timing is a rough estimate. Issuing commands to the SDRAM through the `sdcfg1` register is not supported. No EDAC functionality is currently emulated.

The FTMCTRL for the PROM and I/O areas is also emulated. No EDAC functionality is currently emulated.

4.4.7. IOMMU

Two modes of protection are supported, access protection vector (APV) and MMU mode. Diagnostic accesses and error injection are not supported. But most diagnostic functionality is supported by commands, such as displaying the contents of the cache, writing cache lines/tags and looking up address translations.

4.4.8. CASA instruction

The `-cas` option or any chip option for a chip with CASA support enables emulation of the CASA instruction (LEON3/4 only). Using `-cas 0` can disable CASA support when otherwise already enabled.

4.4.9. SPARC V8 MUL/DIV and V8E MAC instructions

TSIM/LEON4 by default supports the SPARC V8 multiply and divide instructions. To emulate LEON4 systems which do not implement these, use the `-nov8` option to disable multiply and divide instructions. TSIM/LEON4 optionally implements the SPARC V8E MAC instructions. To emulate LEON4 systems which implement these, use the `-mac` option to enable the MAC instructions, and make sure to not use `-nov8`.

4.4.10. FPU emulation

By default, TSIM/LEON4 emulates the GRFPU FPU. See Section 4.1.3 for details on the FPU models.

4.4.11. DSU and hardware breakpoints

The LEON debug support unit (DSU) and the hardware watchpoints (%asr24 - %asr31) are not emulated.

4.4.12. AHB status registers

The AHB status register on the processor bus is modelled. The CE bit will never be set by TSIM's internal memory models, but the `correctable_error()` function (Section 5.3.1) can be used in a user model to set it. Furthermore, the HMASTER field is set to the CPU index (starting at zero) when the CPU caused the error, and 4 when any other master caused the error.

When using `-ahbstatus` or a chip option for a chip that has AHB status registers, AHB status registers are enabled. As TSIM currently does not emulate FT, the CE bit will never be set by TSIM's internal memory models, but the `correctable_error()` function (Section 5.3.1) can be used in a user model to set it. Furthermore, the HMASTER field is set to the CPU index (starting at zero) when the CPU caused the error and one over the last CPU index (i.e. 1 in a one CPU system) when any other master caused the error.

4.4.13. GPTIMER emulation

The debugflag `GPTIMER_ACC` can be used with the TSIM command `gptimerX_dbg` to enable debug printouts each time a register access is made to the core. Here X is the index of the GPTIMER core.

5. Loadable modules

NOTE: At this stage, the available interfaces are not entirely in their final form and are subject to change.

User-defined models using C APIs are all loaded into TSIM using the general module interface, from which the specific user modules can be registered with TSIM using different registration functions.

5.1. General module interface

Connecting a module is done through a user supplied dynamic library that should expose a public symbol `loadable_module` of type `struct loadable_module *`. Note that the module must be compiled to be position-independent, i.e. with the `-fPIC` switch (gcc). To load the module use the `-mod` option. The environmental variable `TSIM_MODULE_PATH` can be set to a ':' separated (';' in WIN64) list of search paths. The `struct loadable_module` is defined in `tsim.h` as:

```
struct loadable_module {
    void *priv; /* Free for the module to use */
    int (*preinit)(struct loadable_module *module);
    int (*init)(struct loadable_module *module);
    void (*exit)(struct loadable_module *module);
    void (*restart)(struct loadable_module *module);
    void (*reset)(struct loadable_module *module);
    void (*preset)(struct loadable_module *module);
    void (*start)(struct loadable_module *module);
    void (*stop)(struct loadable_module *module);
};
```

The elements in the structure has the following meaning:

```
void *priv;
    Free for the module to use.

int (*preinit)(struct loadable_module *module);
    Called once before simulator startup. Startup options should be registered here. See Section 5.5.

int (*init)(struct loadable_module *module);
    Called once on simulator startup. Modules should be registered here.

void (*exit)(struct loadable_module *module);
    Called once on simulator exit.

void (*restart)(struct loadable_module *module);
    Called every time the simulator is restarted (simtime set to zero) including at startup. After a restart TSIM
    will also issue a call to reset.

void (*reset)(struct loadable_module *module);
    Called every time the system is reset, including at startup and after a restart.

void (*preset)(struct loadable_module *module);
    Called when the run command performs bootloader-like operations.

void (*start)(struct loadable_module *module);
    Called each time simulation starts, both when starting for the first time using boot or run command and
    when continuing using go, cont, step and the like.

void (*stop)(struct loadable_module *module);
    Called every time simulation stops, e.g. due to breakpoints, user pressing Ctrl-C, etc.
```

5.1.1. Connecting specific modules

Specific modules should be registered from the `init` function of a general module. The following functions are used for that:

```
tsim_register_ahb_module(struct ahb_subsystem *ahbsystem)
    Register an AHB system module. See Section 5.3.

tsim_register_io_module(struct io_subsystem *iosystem)
    Register a I/O system module. See Section 5.4.

tsim_register_spim_module(struct spim_subsystem *subsystem, int index)
    Register subsystem to SPIM controller with index index. See Chapter 22.

tsim_register_gpio_module(struct gpio_input *inp, int index)
    Register inp to GPIO controller with index index. See Chapter 17.
```

```
tsim_register_spi_module(struct spi_input *inp, int index)
    Register inp to SPI controller with index index. See Chapter 21.
tsim_register_dac_module(struct dac_input *inp, int index)
    Register inp to DAC controller with index index. See Section 8.3.
tsim_register_can_node(struct can_node *node, int canbus_index)
    Register node to CAN bus with index canbus_index. See Section 14.4 for more information.
tsim_register_grpci_module(struct grpci_input *inp, int index)
    Register inp to GRPCI controller with index index. See Section 18.3 for more information.
```

5.1.2. General module examples

As all user modules are loaded through the general module interface, all the examples pointed out in Section 5.7. Of those, the `walltimesync.c` example is a pure general module example that does not register another type of module.

5.2. TSIM exported emulation interfaces

TSIM exports three structures: `simif`, `ioif` and `procif`. The `simif` structure defines functions and data structures belonging to the simulator core, while `ioif` defines functions for bus accesses. The `procif` structure defines a few functions giving access to the processor emulation, cache behaviour and interrupt controller.

Note that in general the exported functions in these structures may only be called from user module functions that are called by TSIM, e.g. the `init` function, from event callbacks, from read and write functions, as well as from TLIB. Unless explicitly allowed, do not call them from a separate thread or a signal handler.

Pointers to `simif`, `ioif` and `procif` can be obtained by the functions `tsim_get_simif()`, `tsim_get_ioif()` and `tsim_get_procif()` defined in `tsim.h`.

5.2.1. simif structure

The `simif` structure is defined in `tsim.h` as:

```
struct sim_options {
    uint32 phys_ram;
    uint32 phys_rom;
    float64 freq;
    float64 wdfreq;
    uint32 phys_sdram;
};
struct sim_interface {
    struct sim_options *options; /* tsim command-line options */
    uint64 *simtime; /* current simulator time */
    void (*event)(void (*cfunc)(), uint32 arg, uint64 offset);
    int (*stop_event)(void (*cfunc)());
    int *irl; /* interrupt request level */
    void (*sys_reset)(); /* reset processor */
    void (*sim_stop)(); /* stop simulation */
    int (*stop_event_arg)(void (*cfunc)(), int arg, int op);

    /* Restorable events */
    unsigned short (*reg_revent)(void (*cfunc) (unsigned long arg));
    unsigned short (*reg_revent_prearg)(void (*cfunc) (unsigned long arg),
                                        unsigned long arg);
    int (*revent)(unsigned short index, unsigned long arg, uint64 offset);
    int (*revent_prearg)(unsigned short index, uint64 offset);
    int (*stop_revent)(unsigned short index);
    int (*lprintf)(const char *format, ...); /* logged formatted output */
    int (*vprintf)(const char *format, va_list ap); /* logged formatted output */

    /* Collected arguments from all sources, excluding executable name */
    int argc;
    char **argv;
};
```

The elements in the structure has the following meaning:

```
struct sim_options *options;
    Contains some tsim startup options. options.freq defines the clock frequency of the emulated processor and can be used to correlate the simulator time to the real time.
```

```
uint64 *simtime;
```

Contains the current simulator time. Time is counted in clock cycles since start of simulation. To calculate the elapsed real time, divide simtime with options.freq.

```
void (*event)(void (*cfunc)(), int arg, uint64 offset);
```

TSIM maintains an event queue to emulate time-dependent functions. The event () function inserts an event in the event queue. An event consists of a function to be called when the event expires, an argument with which the function is called, and an offset (relative the current time) defining when the event should expire.

NOTE: The event () function may only be called from event callbacks or at start of simulation (e.g. not from from from a separate thread or a signal handler). The event queue can hold a maximum of 2048 events.

NOTE: For save and restore support, restorable events should be used instead.

```
int (*stop_event)(void (*cfunc)());
```

stop_event () will remove all events from the event queue which has the calling function equal to cfunc (). Returns the number of events stopped.

```
int *irl;
```

Current IU interrupt level. Should not be unless in a model for something that explicitly monitor theses lines.

```
void (*sys_reset)();
```

Performs a system reset. Should only be used if the model is capable of driving the reset input.

```
void (*sim_stop)();
```

Stops current simulation. Can be used for debugging purposes if manual intervention is needed after a certain event.

```
int (*stop_event_arg)(void (*cfunc)(),int arg,int op);
```

Similar to stop_event () but differentiates between 2 events with same cfunc but with different arg given when inserted into the event queue via event (). Used when simulating multiple instances of an entity. Parameter op should be 1 to enable the arg check. Returns the number of events stopped.

```
unsigned short (*reg_revent)(void (*cfunc) (unsigned long arg));
```

Registers a restorable event that will use cfunc as callback. The returned index should be used when calling revent (). The event argument is supplied when calling revent (). The call to reg_revent () should be done once at module initialisation.

```
unsigned short (*reg_revent_prearg)(void (*cfunc) (unsigned long arg), unsigned long arg);
```

Registers a restorable event that will use cfunc as callback and arg as argument. This can be used to register an argument that is a pointer to a data structure. The returned index should be used when calling revent_prearg (). The call to reg_revent_prearg () should be done once at module initialisation.

```
int (*revent)(unsigned short index, unsigned long arg, uint64 offset);
```

This inserts an event registered by reg_revent () into the event queue with the registered cfunc for the given index. Multiple events with the same index can be in the event queue at the same time. The arg and offset arguments are the same as for the event () function.

NOTE: See the description of event () for limitations on number of events and from which contexts events can be added.

```
int (*revent_prearg)(unsigned short index, uint64 offset);
```

This inserts an event registered by reg_revent_prearg () into the event queue with the registered cfunc and arg for the given index. Multiple events with the same index can be in the event queue at the same time. The offset argument is the same as for the event () function.

NOTE: See the description of event () for limitations on number of events and from which contexts events can be added.

```
int (*stop_revent)(unsigned short index);
```

This removes all events from the event queue that has been entered by revent () or revent_prearg () using the given index. Returns the number of events stopped.

```
int (*lprintf)(const char *format, ...)
```

Function for formatted output that goes both to stdout and, when logging is enabled, to the log. The function interface works like for printf.

```
int (*vfprintf)(const char *format, va_list ap)
```

Function for formatted output that goes both to stdout and, when logging is enabled, to the log. The function interface works like for vprintf.

```
int argc, char** argv
```

argv is the collected arguments from all sources, excluding executable name. argc is the number of arguments.

5.2.2. ioif structure

The ioif structure is defined in tsim.h as:

```
struct io_interface {
    void (*set_irq)(uint32 irq);
    int (*dma_read)(uint32 master_id, uint32 addr, uint32 *data, int num);
    int (*dma_write)(uint32 master_id, uint32 addr, uint32 *data, int num);
    int (*dma_write_sub)(uint32 master_id, uint32 addr, uint32 *data, int sz);
};
```

The elements of the structure have the following meaning:

```
void (*set_irq)(uint32 irq);
```

Generate interrupt *irq* on the bus. Valid values of *irq* is 1 - 15 for systems without extended interrupts and 1-31 for systems with extended interrupts, and 1-63 for GR716. Note that the interrupt controller controls how and when processor interrupts are actually generated.

```
int (*dma_read)(uint32 master_id, uint32 addr, uint32 *data, int num);
```

```
int (*dma_write)(uint32 master_id, uint32 addr, uint32 *data, int num);
```

Performs DMA transactions to/from the emulated processor memory. Only 32-bit word transfers are allowed, and the address must be word aligned. On bus error, 1 is returned, otherwise 0. DMA takes place on the AMBA AHB bus.

```
int (*dma_write_sub)(uint32 master_id, uint32 addr, uint32 *data, int sz);
```

Performs DMA transactions to/from the emulated processor memory on the AMBA AHB bus. On bus error, 1 is returned, otherwise 0. Write size is indicated by *sz* as follows: 0 = byte, 1 = half-word, 2 = word, 3 = double-word.

5.2.3. procif structure

The procif structure is defined in tsim.h as:

```
struct proc_interface {
    void (*set_irl)(int cpuid, int level); /* Generate external interrupt signal directly to CPU */
    void (*cache_snoop)(uint32 addr);
    void (*cctrl)(int cpuid, uint32 *data, uint32 read);
    void (*power_down)(int cpuid);
    void (*set_irq_level)(uint32 irq, int set);
    void (*set_irq)(uint32 irq); /* generate external interrupt */
};
```

The elements in the structure have the following meaning:

```
void (*set_irl)(int cpuid, int level);
```

Set the the current interrupt level (*ui.irl* in VHDL model) signal directly to the specified CPU. Allowed values are 0 - 15, with 0 meaning no pending interrupt. Once the interrupt level is set, it will remain until it is changed by a new call to *set_irl()*. The modules interrupt callback routine should typically reset the interrupt level to avoid new interrupts.

NOTE: For normal interrupt generation, use *set_irq* instead. This bypasses the built in interrupt controller model.

```
void (*cache_snoop)(uint32 addr);
```

The *cache_snoop()* function can be used to invalidate data cache lines (regardless of whether data cache snooping is enabled or not). The tags to the given address will be checked, and if a match is detected the corresponding cache lines will be flushed (i.e. the tag will be cleared). If an MMU is present and is enabled the argument should be a virtual address. See also the *snoop* function in *struct ahb_interface*.

```
void (*cctrl)(int cpuid, uint32 *data, uint32 read);
```

Read and write the specified CPUs cache control register (CCR). If read = 1, the CCR value is returned in *data, else the value of *data is written to the CCR.

```
void (*power_down)(int cpuid);
```

The specified processor enters power down-mode when called.

```
void (*set_irq_level)(uint32 irq, int set);
```

This is used to generate level interrupts. When calling set_irq_level with set set to 1 this enables a constant generation of interrupt irq that remains active until a subsequent call to set_irq_level with the same irq value and with set set to 0.

```
void (*set_irq)(uint32 irq);
```

Generate interrupt irq on the bus. Valid values of irq is 1 - 15 for systems without extended interrupts and 1-31 for systems with extended interrupts, and 1-63 for GR716. Note that the interrupt controller controls how and when processor interrupts are actually generated.

5.3. LEON AHB emulation interface

TSIM allows user defined AHB modules simulating devices on the AMBA buses (both AHB and APB). The emulated processor core communicates with an AHB module using an interface similar to the AHB master interface in the real LEON VHDL model. As the real processor, the simulator primarily interacts with the emulated device through read and write requests, while the emulated device can optionally generate interrupts and DMA requests.

To load and register an AHB system, the general module interface should be used to load it in, and from the general module init function call tsim_register_ahb_module() to register the AHB system. The ahb_subsystem struct is described in Section 5.3.1.

The AHB module interface is made up of two parts; one that is exported by the AHB module and allows TSIM to access the emulated AHB devices; and one that is filled in by TSIM and defines TSIM functions and data structures that can be used by the AHB module. The data structures documented in Section 5.2 can also be used by the AHB module. The information there about from where those functions are allowed to be called applies to the TSIM provided function in the AHB module interface as well.

To register memory areas, use the add_ahb_slave and/or add_apb_slave functions. Whenever an access to that memory area is performed either the registered read or write callback will be called. To be able to use the **load** or **blload** command, a function get_mem_ptr needs to be registered when adding an AHB slave. This function should return a pointer to the module's internal underlying memory. The AHB module can use the add_ahb_pp and add_apb_pp functions to register plug&play entries that will show up in plug&play areas and thus can be seen during plug&play-scanning. Memory areas and plug&play entries should be registered from the ahb_subsystem init function.

5.3.1. Structure to be provided by AHB module

tsim.h defines the ahb_subsystem structure to be provided by the emulated AHB module:

```
struct ahb_subsystem {
    /* --- Initialed by module --- */
    void (*init)(void);
    void (*exit)(void);
    void (*reset)(void);
    void (*restart)(void);
    int (*intack)(int level);
    void (*intpend)(unsigned int pend);
    void (*start)(void);
    void (*stop)(void);

    /* --- Initialised by TSIM --- */
    void (*correctable_error)(uint32 addr, uint32 master, uint32 size, int write);
    int (*add_apb_slave)(uint32 base,
                        uint32 size,
                        void *priv,
                        int (*read)(void *priv, uint32 addr, uint32 *data),
                        int (*write)(void *priv, uint32 addr, uint32 data));
    int (*add_ahb_slave)(uint32 base,
                        uint32 size,
                        int cacheable,
                        void *priv,
                        uint8 *(*get_mem_ptr)(void *priv, uint32 base, uint32 size),
```

```

        int (*read)(void *priv, struct ahb_access *access),
        int (*write)(void *priv, struct ahb_access *access));
void (*add_apb_pp)(uint32 vendor, uint32 device,
                  uint32 version, uint32 irq,
                  uint32 absolute_address,
                  uint32 absolute_mask);
uint32 (*build_ahb_id)(uint32 vendor, uint32 device, uint32 version,
                      uint32 irq);
uint32 (*build_ahb_membar)(uint32 start, uint32 size,
                          int cacheable, int prefetchable);
uint32 (*build_ahb_iobar)(uint32 start, uint32 size,
                          int cacheable, int prefetchable);
void (*add_ahb_pp)(int master, uint32 id,
                  uint32 bar0, uint32 bar1, uint32 bar2, uint32 bar3);
};

```

5.3.1.1. Elements initialised by module

The elements of the structure initialised by modules have the following meanings:

```

void (*init)(void);
    Called once on simulator startup. Set to NULL if unused.
void (*exit)();
    Called once on simulator exit. Set to NULL if unused.
void (*reset)();
    Called every time the system is reset, including at startup and restart. Set to NULL if unused.
void (*restart)();
    Called every time the simulator is restarted (simtime set to zero). Set to NULL if unused.
int (*intack)(int level);
    intack() is called when the processor takes an interrupt trap (tt = 0x11 - 0x1f). The level of the taken
    interrupt is passed in level. This callback can be used to implement interrupt controllers. intack() should
    return 1 if the interrupt acknowledgement was handled by the AHB module, otherwise 0. If 0 is returned,
    the default LEON interrupt controller will receive the intack instead.
void (*intpend)(unsigned int pend);
    Leon3/4 only: The intpend() function is called when the set of pending interrupts changes. The pend
    argument is a bitmask with the bits of pending interrupts set to 1.
void (*start)(void)
    Called each time simulation starts, both when starting for the first time using boot or run command and
    when continuing using go, cont, step and the like.
void (*stop)(void)
    Called every time simulation stops, e.g. due to breakpoints, user pressing Ctrl-C, etc.

```

5.3.1.2. Elements initialised by TSIM

The elements of the structure initialised by TSIM have the following meanings:

```

struct sim_interface *simif;
    Entry simif is initialised by tsim with the global struct sim_interface structure.
void (*snoop)(unsigned int addr)
    The callback snoop is initialised by tsim. If data cache snooping is enabled (and functioning, i.e. not
    UT699) it flushes (i.e. invalidates) data cache lines corresponding to physical address addr (on LEON3/4
    even when MMU is enabled). If the AHB module is doing DMA writes directly to memory pointers, it is
    the responsibility of the AHB module to call this for all changed words for snooping to work correctly.
struct io_interface *io;
    Initialised with the I/O interface structure pointer.
void (*dprint)(char *);
    Initialised by tsim with a callback pointer to the debug output function. Output ends up in log, when logging
    is enabled and gets forwarded to gdb when running TSIM via gdb. See lprintf and vlprintf for the
    formatted counterparts.
struct proc_interface *proc;
    Initialised with the procif structure pointer.
int (*lprintf)(const char *format, ...)
    Initialised by TSIM with a function for formatted output that goes both to stdout and, when logging, to the
    log. The function interface works like for printf.

```

```
int (*vfprintf)(const char *format, va_list ap)
```

Initialised by TSIM with a function for formatted output that goes both to stdout and, when logging is enabled, to the log. The function interface works like for vprintf.

```
void correctable_error(uint32 addr, uint32 master, uint32 size, int write)
```

Can be called by an AHB module to signal a correctable error to an AHBSTAT core (if present) or a LEON2 memstat. It is intended to be called during handling of a successful read or write. The parameters to supply corresponds to the register fields to the AHBSTAT registers or LEON2 FAILAR/FAILSR registers (the *rw* field in LEON2 FAILSR corresponding to !write).

```
int (*add_apb_slave)(uint32 base, uint32 size, void *priv, int (*read)(void
*priv, uint32 addr, uint32 *data), int (*write)(void *priv, uint32 addr,
uint32 data));
```

Registers an APB slave. The *base* parameter is the start address of the area, *size* is the size of the area (in bytes). The *priv* parameter is a pointer that can be set freely by the user and is provided to calls to the *read* and *write* functions. The registered read and write functions are called on bus reads and writes from and to the registered memory area respectively. APB slave models (in contrast to AHB slave models) do not need to be concerned about access timing, different write sizes or number of multiple word reads. Those things are handled by the APB controller model. The APB slave only handles single word reads and single word writes.

The *read* function is called for reads from the registered area. The *priv* argument is the pointer registered in the *add_apb_slave* call. The *addr* parameter contains the address of the single word read. The *data* parameter points to a buffer where the read data should be placed into on a successful read. The function should return 0 for a successful access or 1 for a failed access.

The *write* function is called for writes to the registered area. The *priv* argument is the pointer registered in the *add_apb_slave* call. The *addr* parameter contains the address of the single word write. The *data* parameter contains the word that is written. The function should return 0 for a successful access or 1 for a failed access.

```
int (*add_ahb_slave)(uint32 base, uint32 size, int cacheable, void *priv,
uint8 *(*get_mem_ptr)(void *priv, uint32 base, uint32 size), int (*read)
(void *priv, struct ahb_access *access), int (*write)(void *priv, struct
ahb_access *access))
```

Registers an AHB slave. Here, *base* is the start address of the area, *size* is the size of the area (in bytes), *cacheable* indicates if the area is cacheable or not. The *priv* parameter can be set freely by the user and is provided to calls to the *read* and *write* functions. Details on the *read*, *write* and *get_mem_ptr* functions are described in Section 5.3.1.3.

```
void (*add_apb_pp)(uint32 vendor, uint32 device, uint32 version, uint32
irq, uint32 absolute_address, uint32 absolute_mask)
```

Add APB plug&play entry. Here, *vendor* is the vendor ID of the device, *device* is the device ID and *version* is the device version. The *irq* parameter is the registered device IRQ. The *absolute_address* parameter is the base address of the area. *absolute_mask* is the address mask, usually the size of the area in bytes - 1.

```
uint32 (*build_ahb_id)(uint32 vendor, uint32 device, uint32 version, uint32
irq)
```

Helper function to build a plug&play ID.

```
uint32 (*build_ahb_membar)(uint32 start, uint32 size, int cacheable, int
prefetchable)
```

Helper function to build a plug&play bar. Here, *start* is the beginning of the area, *size* is the size. *cacheable* indicates if the area is cacheable and *prefetchable* indicates if the area is prefetchable.

```
uint32 (*build_ahb_iobar)(uint32 start, uint32 size, int cacheable, int
prefetchable)
```

Helper function to build a plug&play bar. *start* is the beginning of the area, *size* is the size. *cacheable* indicates if the area is cacheable and *prefetchable* indicates if the area is prefetchable.

```
void (*add_ahb_pp)(int master, uint32 id, uint32 bar0, uint32 bar1, uint32
bar2, uint32 bar3)
```

Register an AHB plug&play entry. Above helper functions can be used to fill out the different bars. The *master* argument should be 1 when registering an entry for an AHB master and 0 when registering an AHB

slave. The *build_ahb_id* helper function can be used for building the *id*, and the *build_ahb_iobar* and *build_ahb_membar* helper functions can be used for building the different bars.

5.3.1.3. Callbacks for AHB module AHB slaves

For AHB slaves, read and write callback functions is registered using *add_ahb_slave* to handle reads and writes from and to the registered memory area. It is also possible to register a *get_mem_ptr* to allow access to emulated memory. That is required for e.g. load to work against user emulated memory. Note that for APB slaves, a slightly different interface is used.

```
struct ahb_access {
    uint32 address;
    uint32 *data;
    uint32 ws;
    uint32 rnum;
    uint32 wsize;
};

/* Callbacks */
int (*read)(void *priv, struct ahb_access *access)
int (*write)(void *priv, struct ahb_access *access)
uint8 *(*get_mem_ptr)(void *priv, uint32 base, uint32 size)
```

AMBA slave read function. The registered read function is called on bus reads from the registered memory area. The *priv* argument is a pointer to the private data used when the area was registered. A read is always treated as a read of one or more 32-bit words. The *access->addr* field contains the address of the first word to read. The *access->data* field points to a buffer that should be filled in with the read data on a successful read. The *access->ws* field should be set by the module to the number of cycles for the complete access. The *access->rnum* field contains the number of words to be read. The function should return 0 for a successful access or 1 for a failed access. The *access->wsize* field is not used for reads.

AMBA slave write function. The registered write function is called on bus writes to the registered memory area. The *priv* argument is a pointer to the private data used when the area was registered. The *access->addr* field contains the address of the write. The *access->data* field points to the data to write; either one word for a byte, half word or word write, or two words for double-word writes. The *access->wsize* field defines write size as follows: 0 = byte, 1 = half-word, 2 = word, 3 = double-word (no other sizes are valid). The *access->ws* field should be set by the module to the number of cycles for the complete access. The function should return 0 for a successful access and 1 for failed access. The *access->rnum* field is not used for writes.

AHB slave get_mem_ptr function. During file load operations, TSIM will access emulated memory through a memory pointer. Such a pointer can be returned from user emulated memory via the *get_mem_ptr* function. Without such a pointer, loads can not be performed to user emulated memory. When this function is available it can also be used by TSIM for other non-simulation accesses like when displaying memory contents. The *priv* argument is the private data pointer used when the area was registered. The *base* parameter is the base address of the area and *size* parameter is the size of the area requested (in bytes). The function should return a character pointer to the emulated memory array if the address and size is totally within the range of the emulated memory. If outside the range, NULL should be returned. Set this callback to NULL if not used.

5.3.2. Big versus little endianness

SPARC conforms to the big endian byte ordering. This means that the most significant byte of a (half) word has lowest address. To execute efficiently on little-endian hosts (such as Intel x86 PCs), emulated memory is organised on word basis with the bytes within a word arranged according the endianness of the host. Read cycles can then be performed without any conversion since SPARC always reads a full 32-bit word. During byte and half word writes, care must be taken to insert the written data properly into the emulated memory. On a byte-write to address 0, the written byte should be inserted at address 3, since this is the most significant byte according to little endian. Similarly, on a half-word write to bytes 0/1, bytes 2/3 should be written.

5.3.3. AHB module example

See the *ahb.c* example pointed out in Section 5.7.

5.3.4. AHB module limitations

Currently there is no support for user defined AHB modules to override accesses to a builtin I/O core model in TSIM. This will be made possible in an upcoming release.

5.4. I/O module interface

The AHB module system is the primary way to add user models for bus devices. The I/O device interface can be used to add a module to the I/O bus behind the memory controller (when present in the system) or to act as a fallback taking care of accesses for areas that are not modelled by anyone. If neither TSIM or any AHB module handles a memory access it will be forwarded to an I/O module if present. To register an I/O module, call `tsim_register_io_module(iosystem)` from the `init` function of a `loadable_module` struct, see Section 5.1. There can be only one I/O module.

The `io_subsystem` struct is described below.

```
struct io_subsystem {
    void (*io_init)(void); /* start-up */
    void (*io_exit)();      /* called once on exit */
    void (*io_reset)();     /* called on processor reset */
    void (*io_restart)();   /* called on simulator restart */
    int (*io_read)(unsigned int addr, int *data, int *ws);
    int (*io_write)(unsigned int addr, int *data, int *ws, int size);
    char *(*get_io_ptr)(unsigned int addr, int size);
};
```

The elements of the structure have the following meanings:

```
void (*io_init)(void);
    Called once on simulator startup. Set to NULL if unused.

void (*io_exit)();
    Called once on simulator exit. Set to NULL if unused.

void (*io_reset)();
    Called every time the system is reset, including at startup and restart. Set to NULL if unused.

void (*io_restart)();
    Called every time the simulator is restarted (simtime set to zero). Set to NULL if unused.

int (*io_read)(unsigned int addr, int *data, int *ws);
    Processor read call. The processor always reads one full 32-bit word from addr. The data should be returned in *data, the number of waitstates should be returned in *ws. If the access would fail (illegal address etc.), 1 should be returned, on success 0.

int (*io_write)(unsigned int addr, int *data, int *ws, int size);
    Processor write call. The size of the written data is indicated in size: 0 = byte, 1 = half-word, 2 = word, 3 = double-word. The address is provided in addr, and is always aligned with respect to the size of the written data. The number of waitstates should be returned in *ws. If the access would fail (illegal address etc.), 1 should be returned, on success 0.

char * (*get_io_ptr)(unsigned int addr, int size);
    TSIM can access emulated memory in the I/O device in two ways: either through the io_read/io_write functions or directly through a memory pointer. get_io_ptr() is called with the target address and transfer size (in bytes), and should return a character pointer to the emulated memory array if the address and size is within the range of the emulated memory. If outside the range, NULL should be returned. Set to NULL if not used.
```

5.5. Adding startup options

A module can register a startup option by filling in a `struct user_option` and calling the `tsim_register_user_option` function which will return 0 on success and 1 on failure to register the option.

```
struct user_option {
    /* User defined private pointer*/
    void *arg;
    /* Called when the option is parsed */
    int (*option_execute)(void *arg, int argc, const char **argv);
    const char *name; /* Name of the option */
};
```

```

const char *help_online; /* One line description */
const char *help_full; /* Complete description */
const char *help_syntax; /* Description of option syntax */
};

int tsim_register_user_option(struct user_option *user_option);

```

The *name* pointer must be set to a unique option name, and the *option_execute* pointer to a callback function. The *option_execute* callback will be called when the option is parsed at simulator startup and will get the registered *arg* as first parameter with the number of startup arguments in *argc* and the arguments in the *argv* array. The option name itself is included in the count and is the first entry of the array. The return value from *option_execute* should be how many arguments the option parsed, e.g. 1 if no arguments other than the option itself, or 2 if another parameter was parsed.

The *help_online*, *help_full* and *help_syntax* pointers can be set to a oneline description of the option, a full documentation of the option and if the option takes any arguments the syntax can be set, in order for the options to be supported by the *-help* option.

5.6. Adding user commands

A module can register a user command by filling in a struct `user_cmd` and calling the `tsim_register_user_cmd` function which will return 0 on success and 1 on failure to register the command.

```

struct user_cmd {
    /* User defined private pointer */
    void *arg;
    /* Called when the command is executed */
    int (*cmd_execute)(void *arg, int argc, char **argv);
    /* Called on unregistration of commands */
    void (*cmd_unregister)(void *arg);
    const char *name; /* Name of the command */
    const char *help_online; /* One line description */
    const char *help_full; /* Complete description */
    const char *help_syntax; /* Description of command syntax */
};

int tsim_register_user_cmd(struct user_cmd *user_cmd);

```

The *name* pointer must be set to a unique command name, and the *cmd_execute* pointer to a callback function. The *cmd_execute* callback will be called when the command is evaluated and will get the registered *arg* as first parameter with the number of command arguments in *argv* and the arguments in the *argv* array. The command name itself is included in the count and is the first entry of the array. The return value from *cmd_execute* becomes a signed integer Tcl return value.

The *help_online*, *help_full* and *help_syntax* pointers can be set to a oneline description of the command, a full documentation of the command and if the command takes any arguments the syntax can be set, in order for the command to be supported by the **help** command. The *cmd_unregister* pointer can optionally be set to be called when TSIM exits, e.g. if cleanup needs to be done.

5.7. Loadable modules distributed with TSIM

The following table shows which loadable modules are distributed with which TSIM versions.

Table 5.1. Loadable modules distributed with TSIM

Module	File	For TSIM versions
AHB module example	examples/modules/ahb.c	All
I/O module example	examples/modules/io.c	All
Walltime synchronisation example	examples/modules/walltimesync.c	All
CAN node example	examples/input/can_node.c	LEON3/4
GPIO input example	examples/input/gpio.c	LEON3/4
SPI slave example	examples/input/spi.c	LEON3/4

Module	File	For TSIM versions
SPI memory example	examples/input/spim.c	LEON3
PCI target example	examples/input/pci_target.c	LEON3
<i>TPS VxWorks 6.x AHB Module</i>	tps/linux-x64/tps.so tps/win64/tps.dll	LEON3/4

The example modules that are provided in source also comes with make files to build them. The example modules in `examples/input` also has usage examples in the `examples/input/README.txt`.

6. TSIM library (TLIB)

TSIM library (TLIB) is not currently available, but will be made available in a future release.

7. Cobham Gaisler GR712RC emulation

To emulate the GR712RC chip the `-gr712rc` option should be used.

The following table lists which cores in the GR712RC are modelled by TSIM or not. The table contains some notes of some unsupported features for otherwise supported cores, but is not necessarily exhaustive in this respect.

Table 7.1. Simulation models for GR712RC

Core	Status	Notes
LEON3FT	Supported by core TSIM3	Both CPUs are modelled. No FT features are modelled.
GRFPU	Supported by core TSIM3	Does not simulate the possibility of multiple outstanding floating point operations.
AHBSTAT	Supported by core TSIM3	
APBCTRL	Supported by core TSIM3	
APBUART	Supported by core TSIM3	
FTMCTRL	Supported by core TSIM3	No FT features are modelled
GPTIMER	Supported by core TSIM3	No Watchdog support.
GRTIMER	Supported by core TSIM3	
IRQMP	Supported by core TSIM3	
CAN_OC	Supported by core TSIM3	See Chapter 15.
FTAHBRAM	Supported by core TSIM3	No FT features are modelled.
GRETH	Supported by core TSIM3	See Chapter 16.
GRGPIO	Supported by core TSIM3	See Chapter 17.
GRSPW2	Supported by core TSIM3	See Chapter 20.
SPICTRL	Supported by core TSIM3	See Chapter 21.
CANMUX	Dummy in TSIM3	Functionality-less registers only
CLKGATE	Dummy in TSIM3	Functionality-less registers only
GRGPREG	Dummy in TSIM3	Functionality-less registers only
B1553BRM	Not supported	
GRASCS	Not supported	
GRSLINK	Not supported	
GRTC	Not supported	
GRTM	Not supported	
I2CMST	Not supported	
AHBJTAG	Not supported	Debug link
DSU3	Not supported	Debug unit

TSIM supports running user defined models for unsupported cores.

7.1. Clock Gating Unit, CANMUX and GRGPREG

The Clock Gate Unit, CANMUX and GRGPREG I/O registers and AMBA Plug & Play area are present in the GR712RC module. Some of the logic to control which bits are implemented, readable and writable etc. is implemented. However the register bits has no functionality. The current register values can be used by custom I/O modules in SW validation. For example checking that accessing a specific address are has not been clock gate disabled or that the SpW clock PLL match with the expect value after initialisation.

8. Cobham Gaisler GR716 emulation

To emulate the GR716 chip the `-gr716` option should be used. When using the GR716 only release, TSIM only simulates GR716 and the `-gr716` option is implicit.

Table 8.1. Simulation models for GR716

Core	Notes and model limitations
AHBROM	GR716 Boot ROM. See Section 8.1.
AHBSTAT	Only the AHB Status Register for the main AMBA bus supported
APBCTRL	Atomic operations supported.
APBUART	Transmitter shift register empty interrupt, delayed interrupt and using two stop bits currently not supported.
LRAM	Atomic operations and DMA accesses supported. Configuration registers are implemented as dummy registers, see Section 8.2.
FTMCTRL	EDAC not supported.
GPTIMER	No Watchdog support.
GRCAN	See Chapter 14 for details about the CAN bus.
GRGPIO	See Chapter 17. Pulse sampler and Pulse sequencer are not currently supported. Atomic operations supported.
GRGPREG	Only bootstrap register implemented.
GRSPW2	See Chapter 20 for details and limitations.
IRQMP	Watchdog control and Error mode status register currently not implemented.
LEON3FT	No FT features are modelled. ZeroJitter, Alternative Window Pointer and REX ISA not currently supported. Register window partitioning is supported.
SPICTRL	See Chapter 21. Automatic Slave select, ThreeWire mode and Slave mode are not currently supported.
SPIMCTRL	See Chapter 22. EDAC not supported.
DAC	See Section 8.3.

GR716 has tightly coupled dual-port local data and instruction RAM. GR716 does not have cache memories. Some register areas for devices that are not emulated are implemented as dummy registers. See Section 8.2. TSIM does not emulate the DSU, L3STAT and AHBTRACE cores but provide a lot of corresponding functionality and information via TSIM commands instead.

8.1. GR716 Boot ROM

In addition to running RAM images directly from memory using **load** and **run**, TSIM can simulate a cold start going through the bootloader in the GR716 Boot ROM, with its different boot possibilities, or bypassing the Boot ROM, booting directly from a different source. The **boot** command is used to start simulating a cold start.

The bootloader in the GR716 Boot ROM supports multiple boot sources. Booting from external SRAM, external PROM and external SPI memory is supported. There is currently no built-in model for the I²C controller. Therefore, to support booting an image read over from I²C, a user model for the I²C controller and bus is needed. The bootloader can also set up the GR716 for remote access. However, the remote access mode is currently not supported in TSIM. The bootloader can also be bypassed altogether to boot the GR716 directly from external SPI memory, SRAM or PROM (without going through the bootloader first).

GR716 samples various signals on reset and populates the bootstrap register with the result. TSIM does not simulate this sampling. Instead the user can set the value of the bootstrap register with the `-bootstrap` option. For example, to boot using an application software (ASW) image residing in external PROM, start TSIM with `-bootstrap 0x0000c00a`, load the software image with **load image**, and simulation with **boot** to start execution from the Boot ROM from a reset state.

The following are examples of different bootstrap values that can be used. This is not an exhaustive list. See the GR716 Data Sheet and User's manual for details.

Table 8.2. Boot methods and example bootstrap values

Boot type	Bootstrap value	Notes
External SPI memory boot	0x0000c000	Execution continues directly in SPI memory
External SRAM boot	0x0000c004	Execution continues directly in SRAM
External PROM boot	0x0000c008	Execution continues directly in PROM
External SPI memory ASW boot	0x0000c002	Extracts ASW image from SPI memory
External SRAM ASW boot	0x0000c006	Extracts ASW image from SRAM
External PROM ASW boot	0x0000c00a	Extracts ASW image from PROM
External I ² C memory ASW boot	0x0000c00e	Not supported without user model of I ² C.
Bypass directly to SPI memory	0x1000c000	Execution starts from SPI memory
Bypass directly to SRAM	0x1000c004	Execution starts from SRAM
Bypass directly to PROM	0x1000c008	Execution starts from PROM
Remote access		Currently not supported by TSIM

Note: if the boot sequence fails the boot software will potentially get stuck in a loop and never reach the main application.

8.2. Dummy registers

The following GR716 register areas are in TSIM currently implemented as dummy registers. They can be written to without effect and read from with value 0.

Table 8.3. Dummy register areas in the GR716 model

Address	Name
0x80001000 - 0x800010ff	DLRAM config
0x80006000 - 0x800060ff	Clock gating unit 0
0x80007000 - 0x800070ff	Clock gating unit 1
0x8000b000 - 0x8000b0ff	ILRAM config
0x8000d000 - 0x8000d0ff	IOMUX config
0x8010c000 - 0x8010c0ff	Brown-Out detection control registers
0x8010d000 - 0x8010d0ff	PLL control registers
0x80307000 - 0x803070ff	NVRAM config

8.3. DAC

TSIM GR716 provides a DAC interface. To connect to TSIM's internal DAC model use `tsim_register_dac_model(dac_input, index)` where `dac_input` is a pointer to a struct `dac_input` (see below), and `index` is the index of the DAC controller to connect to. The struct `dac_input` can be found in `dac_input.h`.

See Chapter 5 for further details on how to connect the user model.

```
struct dac_input {
    void (*dac_output)(double value);
};
```

Table 8.4. struct dac_input members

Parameter	Description
dac_output	Callback set by the user. Will be called each time the DAC controllers output value is changed. <i>value</i> is the DAC output value.

9. Cobham Gaisler GR740 emulation

When starting tsim3-leon4 TSIM emulates the GR740 by default.

Table 9.1. Simulation models for GR740

Core	Notes and model limitations
LEON4	No FT features are modelled. Dynamically configurable L1 cache replacement policy not yet supported.
GRFPU	Does not simulate the possibility of multiple outstanding floating point operations.
AHBSTAT	Only the AHB Status Register for the main AMBA bus supported
APBUART	Transmitter shift register empty interrupt, delayed interrupt and using two stop bits currently not supported.
FTMCTRL	PROM and I/O controller. EDAC and write lead out cycles not supported.
GPTIMER	No Watchdog support.
GRCAN	See Chapter 14 for details about the CAN bus.
GRETH	Currently modelled as a GRETH core, not a GRETH_GBIT core. See Chapter 16.
GRGPIO	See Chapter 17. Pulse sampler and Pulse sequencer are not currently supported.
IRQ(A)MP	Watchdog control and error mode status registers are currently not implemented.
L2 Cache	See Section 4.4.3.
SDCTRL	Timings based on a CPU frequency of 250 or 50 MHz and a memory frequency of either 50 or 100 MHz. No EDAC is supported.
SpaceWire router	Router itself not yet emulated. Emulated by 4 GRSPW2 cores.
GRIOMMU	See Section 4.4.7.
SPICTRL	See Chapter 21. Automatic Slave select, ThreeWire mode and Slave mode are not currently supported.

9.1. Dummy registers

The following GR740 register areas are in TSIM currently implemented as dummy registers. They can be written to without effect and read from with value 0.

Table 9.2. Dummy register areas in the GR740 model

Address	Name
0xffa04000 - 0xffa040ff	Clock gating unit
0xffa09000 - 0xffa090ff	Register for bootstrap signals
0xffa0b000 - 0xffa0b0ff	General purpose register bank

10. Cobham UT699 emulation

To emulate the UT699 chip the `-ut699` option should be used. That sets up parameters for core TSIM to match UT699 and sets snooping as non-functional.

The following table lists which cores in the UT699 are modelled by TSIM or not. The table contains some notes of some unsupported features for otherwise supported cores, but is not necessarily exhaustive in this respect.

Table 10.1. Simulation models for UT699

Core	Status	Notes
LEON3FT	Supported by core TSIM3	No FT features are modelled.
GRFPU	Supported by core TSIM3	Does not simulate the possibility of multiple outstanding floating point operations.
AHBSTAT	Supported by core TSIM3	
APBCTRL	Supported by core TSIM3	
APBUART	Supported by core TSIM3	
FTMCTRL	Supported by core TSIM3	No FT features are modelled
GPTIMER	Supported by core TSIM3	No Watchdog support.
IRQMP	Supported by core TSIM3	
CAN_OC	Supported by core TSIM3	See Chapter 15.
GRETH	Supported by core TSIM3	See Chapter 16.
GRGPIO	Supported by core TSIM3	See Chapter 17.
GRPCI	Supported by core TSIM3	Including DMA controller. See Chapter 17.
GRSPW	Supported by core TSIM3	See Chapter 19.
CLKGATE	Not supported	
AHBJTAG	Not supported	Debug link
AHBUART	Not supported	Debug link
DSU3	Not supported	Debug unit

TSIM supports running user defined models for unsupported cores.

11. Cobham UT699E emulation

To emulate the UT699E chip the `-ut699e` option should be used. That sets up parameters for core TSIM to match UT699E.

The following table lists which cores in the UT699E are modelled by TSIM or not. The table contains some notes of some unsupported features for otherwise supported cores, but is not necessarily exhaustive in this respect.

Table 11.1. Simulation models for UT699E

Core	Status	Notes
LEON3FT	Supported by core TSIM3	No FT features are modelled.
GRFPU	Supported by core TSIM3	Does not simulate the possibility of multiple outstanding floating point operations.
AHBSTAT	Supported by core TSIM3	
APBCTRL	Supported by core TSIM3	
APBUART	Supported by core TSIM3	
FTMCTRL	Supported by core TSIM3	No FT features are modelled
GPTIMER	Supported by core TSIM3	No Watchdog support.
IRQMP	Supported by core TSIM3	
CAN_OC	Supported by core TSIM3	See Chapter 15.
GRETH	Supported by core TSIM3	See Chapter 16.
GRGPIO	Supported by core TSIM3	See Chapter 17.
GRPCI	Supported by core TSIM3	Including DMA controller. See Chapter 18.
GRSPW2	Supported by core TSIM3	See Chapter 20.
CLKGATE	Not supported	
AHBJTAG	Not supported	Debug link
AHBUART	Not supported	Debug link
DSU3	Not supported	Debug unit

TSIM supports running user defined models for unsupported cores.

12. Cobham UT700 emulation

To emulate the UT700 chip the `-ut700` option should be used. That sets up parameters for core TSIM to match UT700.

The following table lists which cores in the UT700 are modelled by TSIM or not. The table contains some notes of some unsupported features for otherwise supported cores, but is not necessarily exhaustive in this respect.

Table 12.1. Simulation models for UT700

Core	Status	Notes
LEON3FT	Supported by core TSIM3	No FT features are modelled.
GRFPU	Supported by core TSIM3	Does not simulate the possibility of multiple outstanding floating point operations.
AHBSTAT	Supported by core TSIM3	
APBCTRL	Supported by core TSIM3	
APBUART	Supported by core TSIM3	
FTMCTRL	Supported by core TSIM3	No FT features are modelled
GPTIMER	Supported by core TSIM3	No Watchdog support.
IRQMP	Supported by core TSIM3	
CAN_OC	Supported by core TSIM3	See Chapter 15.
GRETH	Supported by core TSIM3	See Chapter 16.
GRGPIO	Supported by core TSIM3	See Chapter 17.
GRPCI	Supported by core TSIM3	Including DMA controller. See Chapter 18.
GRSPW2	Supported by core TSIM3	See Chapter 20.
SPICTRL	Supported by core TSIM3	See Chapter 21.
CLKGATE	Not supported	
GR1553B	Not supported	
GRTC	Not supported	
GRTM	Not supported	
AHBJTAG	Not supported	Debug link
AHBUART	Not supported	Debug link
DSU3	Not supported	Debug unit

TSIM supports running user defined models for unsupported cores.

13. Atmel AT697 emulation

To emulate the AT697E chip the `-at697e` option should be used. That sets up parameters for core TSIM3 to match AT697E and enables simulation of the AT697 PCI interface.

The following table lists which cores in the AT697 are modelled by TSIM or not. The table contains some notes of some unsupported features for otherwise supported cores, but is not necessarily exhaustive in this respect. See Chapter 4 for details on the builtin simulation models and Chapter 23 for the PCI model.

Table 13.1. Simulation models for AT697

Core	Status	Notes
LEON2FT	Supported by core TSIM3	No FT features are modelled.
FPU	Supported by core TSIM3	
LEON2 system registers	Supported by core TSIM3	
Interrupt controller	Supported by core TSIM3	
Memory controller	Supported by core TSIM3	No FT features are modelled
UART	Supported by core TSIM3	
PCI	Supported by core TSIM3	See Chapter 23
I/O port	Not supported	Easily modelled in user module
JTAG	Not supported	Debug link
Debug UART	Not supported	Debug link
DSU	Not supported	Debug unit

14. GRCAN

Each GRCAN core are connected to two CAN buses (with the possibility to choose which bus to be active on for each GRCAN core). Default values for the bus index is GRCAN core index * 2 for the main bus and (GRCAN core index * 2) + 1 for the secondary bus. With the exception for GR716 where both GRCAN cores are connected to bus 0 and 1 for the main and secondary bus. TSIM models these buses according to the Section 14.4 API.

See the `examples/test` directory for an example GRCAN test program. This test program can be used together with the example can node found in `examples/input`.

14.1. Start up options

GRCAN core start up options

- `-grcanX_bus0 index`
Sets the index of the main CAN bus for GRCAN core X.
- `-grcanX_bus1 index`
Sets the index of the secondary CAN bus for GRCAN core X.

X in the above commands is the index of the core.

14.2. Commands

GRCAN Commands

- grcanX_dbg** [*flag* | **all** | **clean** | **list**]
Toggle specific flag, set all, clear all, or list debug flags for the given GRCAN core. See Section 14.3 for a list of debug flags.

X in the above commands is the index of the core.

14.3. Debug flags

The following debug flags and debug subcommands are available for the GRCAN cores. The `CAN_*` flags can be used with the **grcanX_dbg** command to toggle individual flags for individual GRCAN cores. The subcommands can be used with the **grcanX_dbg** command to change and list the settings of all flags for individual GRCAN cores.

Table 14.1. GRCAN debug flags

Flag	Trace
CAN_ACC	GRCAN register accesses
CAN_RX	GRCAN received messages
CAN_TX	GRCAN transmitted messages
CAN_IRQ	GRCAN interrupts
all	Set all debug flags for the core
clean	Set none of the debug flags for the core
list	List the current setting of the debug flags for the core

14.4. CAN interface

Currently, this CAN bus model is only used for GRCAN. For emulation of CAN OC in GR712RC, UT699, UT699E and UT700, see Chapter 15.

14.4.1. Connecting a user CAN model

To connect a custom CAN node to TSIM's internal CAN bus use `tsim_register_can_node(node, canbus_index)` where `node` is a pointer to a `struct can_node` (see below), and `canbus_index` is the index of the bus to connect to. Both `struct can_node` and `struct can_msg` can be found in `canbus_input.h`.

See Chapter 5 for further details on how to connect the user model.

14.4.2. CAN model API

The internal CAN bus is available through `struct canbus_interface *canbus` provided by the `init` function of `struct can_node` that is called during simulation startup if it has been registered by using the `tsim_register_can_node` function.

The different structs are described below.

```
struct canbus_interface {
    int (*update)(uint32 bus_id);
};
```

Table 14.2. *struct canbus_interface members*

Parameter	Description
update	Used to update a bus after a change in node status.

```
struct can_node {
    unsigned int id;
    void (*init)(struct can_node *node, struct canbus_interface *canbus);
    int (*rx_callback)(uint32 bus_id, uint32 sender_id, struct can_node *node, struct can_msg msg);
    void (*tx_callback)(uint32 bus_id, struct can_node *node, uint32 error_flags, int num_acks);
    struct can_msg (*get_message)(struct can_node *node);
    void (*status)(struct can_node *node);
    uint32 *wants_to_send;
    uint32 *bus_off;
    uint32 *error_passive;
    uint32 invisible;
    uint32 disconnect;
    void *priv;
};
```

Table 14.3. *struct can_node members*

Parameter	Description
id	The nodes id, each node needs an unique id.
init	Callback called by the CAN bus during simulation start up. Provides the module with a <code>canbus_interface</code> , see above. <code>node</code> is a pointer to the node being initiated.
rx_callback	Callback called by the CAN bus each time a new message is available. Input parameters described below.
tx_callback	Callback called by the CAN bus each time this node has sent a message. Input parameters described below.
get_message	Callback called by the CAN bus when the bus is free and the node wants to send. Should return a <code>can_msg</code> struct
status	Callback called by the CAN bus when printing status. Can optionally be set to print the nodes status at the same time.
wants_to_send	Pointer set by the user indicating if the node wants to send a message or not. If set <code>get_message</code> will be called each time the CAN bus is free
bus_off	Pointer set by the user indicating if the node is in bus off state.
error_passive	Pointer set by the user indicating if the node is in error passive state. Otherwise it is in error active state
invisible	If set the node is invisible on the bus. It will receive all messages via the <code>rx_callback</code> . But cannot acknowledge or flag errors.

Parameter	Description
disconnect	If set the node is disconnected from the CAN bus. It will receive no messages and have no impact on the bus.
priv	Pointer to private data. Can be set freely by the user.

If a node wants to send a message it should set `*wants_to_send` to non-zero and call `canbus.update`. Next time the bus is free `get_message` is called and the node should return a can message of type `struct can_msg`. The internal bus model will then collect messages from each node that wants to send and perform arbitration, the winning message will then be sent.

Table 14.4. *tx_callback parameters*

Parameter	Description
bus_id	Index of the CAN bus which the message was sent on.
node	Pointer to the <code>struct can_node</code> that sent the message.
error_flags	If any receiving node forced an error this flag is set.
num_acks	Number of nodes correctly acked the message.

When a message is sent the `rx_callback` is called for each connected node. To acknowledge this message normally this function should return 0, if an error is detected return an error flag. The `msg.flags` property can be used to check if an error should be forced.

Table 14.5. *rx_callback parameters*

Parameter	Description
bus_id	Index of the CAN bus which the message was received on.
sender_id	ID of the sender node.
node	Pointer to the <code>struct can_node</code> that is receiving the message.
msg	A <code>struct can_msg</code> containing the message.

If a node enters bus off mode or error passive mode, the corresponding property should be set by the user. While the node is in bus off mode it will not be able to send messages but `rx_callback` will still be called to receive messages, it is up to the user model if it wants to discard the message or not, note that if in bus off mode the return value will be ignored.

When a node is done sending messages `*wants_to_send` should be set to zero.

If arbitration is won and all nodes have received the message, the winning nodes `tx_callback` is called. If any error was detected the `error_flags` is set. If arbitration is won the node will not receive it's own message through `rx_callback`. The `priv` pointer is unused by the CAN bus and can be set freely by the user. It can, for example, be used to differentiate between different nodes using the same callback functions or used to add extra properties to the node.

```
struct can_msg {
    uint32 *data;

    uint32 flags;
    uint32 nominal_bitrate;
    uint32 fd_bitrate;
};
```

Table 14.6. *struct can_msg members*

Parameter	Description
data	Pointer to the CAN message data.

Parameter	Description
flags	When transmitting, errors can be forced by this flag. When receiving this indicates if errors has been found
nominal_bitrate	The nominal bit-rate which the message will be sent. Measured in clock cycles per bit.
fd_bitrate	The CAN-FD data bit-rate. Should be left as zero when transmitting ordinary CAN-Messages. Measured in clock cycles per bit.

See the `examples/input` directory for an example can node implementation. The example demonstrates how to set up a basic can node that will receive and acknowledge messages.

14.4.3. Error injections

Errors can be injected by the `uint32 flags` property of `struct can_msg`. When transmitting a message the flags can be set to let a receiver know that it should force an error. When receiving the `rx_callback` can return non-zero to let the transmitter know an error has occurred.

Bit 0-4 and bit 31 is reserved and defined below. Bit 0-4 indicates one of the standard errors, defined by the ISO standard 11898-1:2015 (2nd edition), has occurred. Bit 31 indicates if the error was flagged by an error passive node. Remaining bits can be used freely for system specific flags by the users.

Table 14.7. Error flag definitions

Bit	Description
0	Ack error.
1	Form error.
2	CRC error.
3	Stuff error.
4	Bit error
31	Error flagged by error passive node.

14.4.4. Commands

CAN bus Commands

canbusX_status

Prints the status information on the given CAN bus. Note that this is only used for systems with one or more GRCAN devices, not for CAN_OC.

X in the above commands is the index of the bus.

14.4.5. Debug status

To display the status of an internal CAN bus use the **canbusX_status** command. This command will print the status of each connected node, as well as call the optional status command that can be provided by a user model.

14.4.6. Current limitations

Arbitration loss is not reported to the node, it has to check it manually when receiving by either comparing its own message with the received one.

Each node has to have an unique ID.

15. CAN_OC interface

The UT699, UT699E, UT700 and GR712RC chips contains CAN_OC cores which models the CAN_OC cores available in the chip. For core details and register specification please see the manual for each emulated chip.

15.1. Start up options

CAN_OC core start up options

- can_ocX_connect host:port
Connect CAN_OC core X to packet server to specified server and TCP port.
- can_ocX_server port
Open a packet server for CAN_OC core X on specified TCP port.
- can_ocX_ack [0|1]
Enables waiting for an acknowledgement packet on transmission for CAN_OC core X.

X in the above commands is the index of the core.

15.2. Commands

CAN OC Commands

- can_ocX_connect** host:[port]
Connect CAN_OC core X to packet server to specified server and TCP port.
- can_ocX_server** port
Open a packet server for CAN_OC core X on specified TCP port.
- can_ocX_ack** <0|1>
Specifies whether the CAN_OC core will wait for a acknowledgement packet on transmission. This command should only be issued after a connection has been established.
- can_ocX_status**
Prints out status information for the CAN_OC core.
- can_ocX_dbg** [flag|all|clean|list]
Toggle, set, clear, list debug flags for the CAN_OC core.

X in the above commands is the index of the core.

15.3. Debug flags

The following debug flags and debug subcommands are available for CAN interfaces. The *GAISLER_CAN_OC_** flags can be used with the **can_ocX_dbg** command to toggle individual flags for individual CAN_OC cores and with the **dbg** command to toggle individual flags for all CAN_OC cores. The subcommands can be used with the **can_ocX_dbg** command to change and list the settings of all flags for individual CAN_OC cores.

Table 15.1. CAN debug flags

Flag	Trace
GAISLER_CAN_OC_ACC	CAN_OC register accesses
GAISLER_CAN_OC_RXPACKET	CAN_OC received messages
GAISLER_CAN_OC_TXPACKET	CAN_OC transmitted messages
GAISLER_CAN_OC_ACK	CAN_OC acknowledgements
GAISLER_CAN_OC_IRQ	CAN_OC interrupts
all	Set all debug flags for the core
clean	Set none of the debug flags for the core
list	List the current setting of the debug flags for the core

15.4. Packet server

Each CAN_OC core can be configured independently as a packet server or client using either `-can_ocX_server` or `-can_ocX_connect`. When acting as a server the core can only accept a single connection.

A connection should be set up before starting simulation for the first time, and must not be broken after that. Restarting the simulation will not tear down the connection, nor emptying any socket buffers. The socket based interface does not support any signalling of restart of the simulation. To ensure a clean restart of simulation when using this interface, restarting TSIM entirely and reconnecting socket interfaces is advisable.

15.5. CAN packet server protocol

The protocol used to communicate with the packet server is described below. Four different types of packets are defined according to the table below.

Table 15.2. CAN packet types

Type	Value
Message	0x00
Error counter	0xFD
Acknowledge	0xFE
Acknowledge config	0xFF

15.5.1. CAN message packet format

Used to send and receive CAN messages.

31	0
0x0	LENGTH
31:0	LENGTH, specifies the length of the rest of the packet

CAN message

Byte #	Description	Bits (MSB-LSB)
		7 6 5 4 3 2 1 0
4	Protocol ID = 0	Prot ID 7-0
5	Control	FF RTR - - DLC (max 8 bytes)
6-9	ID (32 bit word in network byte order)	ID 10-0 (bits 31 - 11 ignored for standard frame format) ID 28-0 (bits 31-29 ignored for extended frame format)
10-17	Data byte 1 - DLC	Data byte <i>n</i> 7-0

Figure 15.1. CAN message packet format

15.5.2. Error counter packet format

Used to write the RX and TX error counter of the modelled CAN interface.

31

0

0x0	LENGTH
31:0	LENGTH, specifies the length of the rest of the packet

Error counter packet

Byte #	Field	Description
4	Packet type	Type of packet, 0xFD for error counter packets
5	Register	0 - RX error counter, 1 - TX error counter
6	Value	Value to write to error counter

Figure 15.2. Error counter packet format

15.5.3. Acknowledge packet format

If the acknowledge function has been enabled through the start up option or command the CAN interface will wait for an acknowledge packet each time it transmits a message. To enable the CAN receiver to send acknowledge packets (either NAK or ACK) an acknowledge configuration packet must be sent. This is done automatically by the CAN interface when **can_ocX_ack** is issued.

31

0

0x0	LENGTH
31:0	LENGTH, specifies the length of the rest of the packet

Acknowledge packet

Byte #	Field	Description
4	Packet type	Type of packet, 0xFE for acknowledge packets
5	Ack payload	0 - No acknowledge, 1 - Acknowledge

Figure 15.3. Acknowledge packet format

15.5.4. Acknowledge packet format

This packet is used for enabling/disabling the transmission of acknowledge packets and their payload (ACK or NAK) by the CAN receiver. The CAN transmitter will always wait for an acknowledge if started with - can_ocX_ack or if the **can_ocX_ack** command has been issued.

31

0

0x0	LENGTH
31:0	LENGTH, specifies the length of the rest of the packet

Acknowledge configuration packet

Byte #	Field	Description	
4	Packet type	Type of packet, 0xFF for acknowledge configuration packets	
5	Ack configuration	bit 0	Unused
		bit 1	Ack packet enable, 1 - enabled, 0 - disabled
		bit 2	Set ack packet payload, 1 - ACK, 0 - NAK

Figure 15.4. Acknowledge configuration packet format

16. 10/100 Mbps Ethernet Media Access Controller interface

The Ethernet core simulation model is designed to functionally model the 10/100 Ethernet MAC available in UT699, UT699E, UT700 and GR712RC. For core details and register specification please see the chip manual.

The following features are supported:

- Direct Memory Access
- Interrupts

16.1. Start up options

Ethernet core start up options

- grethX_connect host[:port]
Connect Ethernet core to a packet server at the specified host and port. Default port is 2224.
- grethX_mac X:X:X:X:X:X
Set MAC address of the Ethernet core.

16.2. Commands

GRETH Commands

- grethX_dbg** [flag|all|clean|list]
Toggle specific flag, set all, clear all, or list debug flags for the given GRETH core. See Section 16.3 for a list of debug flags.
- grethX_status**
Prints the status of greth core X.
- grethX_connect** ip
Connect to packet server at ip.
- grethX_ping** ip
Simulate a ping. Packets will be generated by TSIM.
- grethX_dump** file
Dump packets to Ethereal readable file.
- grethX_reconnect** <0/1>
Turn GRETH autoreconnect on or off.

X in the above commands is the index of the core.

16.3. Debug flags

The following debug flags are available for the Ethernet interface. Use the them in conjunction with the **dbgon** command to enable different levels of debug information.

Table 16.1. Ethernet debug flags

Flag	Trace
GAISLER_GRETH_ACC	GRETH accesses
GAISLER_GRETH_L1	GRETH accesses verbose
GAISLER_GRETH_TX	GRETH transmissions
GAISLER_GRETH_RX	GRETH reception
GAISLER_GRETH_RXPACKET	GRETH received packets
GAISLER_GRETH_RXCTRL	GRETH RX packet server protocol
GAISLER_GRETH_RXBDCTRL	GRETH RX buffer descriptors DMA
GAISLER_GRETH_TXBDCTRL	GRETH TX packet server protocol
GAISLER_GRETH_TXPACKET	GRETH transmitted packets

Flag	Trace
GAISLER_GRETH_IRQ	GRETH interrupts

16.4. Ethernet packet server

The simulation model relies on a packet server to receive and transmit the Ethernet packets. The packet server should open a TCP socket which the module can connect to. The Ethernet core is connected to a packet server using the `-grethX_connect` start-up parameter or using the **grethX_connect** command.

A connection should be set up before starting simulation for the first time, and must not be broken after that. Restarting the simulation will not tear down the connection, nor emptying any socket buffers. The socket based interface does not support any signalling of restart of the simulation. To ensure a clean restart of simulation when using this interface, restarting TSIM entirely and reconnecting socket interfaces is advisable.

An example implementation of a packet server, named `greth_config`, is included in TSIM distribution. It uses the TUN/TAP interface in Linux, or the WinPcap library on Windows, to connect the GRETH core to a physical Ethernet LAN. This makes it easy to connect the simulated GRETH core to real hardware. It can provide a throughput in the order of magnitude of 500 to 1000 KiB/sec. See its distributed README for usage instructions.

16.5. Ethernet packet server protocol

Ethernet data packets have the following format. Note that each packet is prepended with a one word length field indicating the length of the packet to come (including its header).

Packet length at offset 0x0:

31 0

LEN

31:0 LEN Length of rest of packet: 4 + number of data bytes

Header at offset 0x4:

31 16 15 8 7 5 4 0

R	IPID	TYPE	R
---	------	------	---

31:16 R Reserved for future use. Must be set to 0.

15:8 IPID IP core ID: 1 for Ethernet

7:5 TYPE Packet type: 0 for data packets

4:0 R Reserved for future use. Must be set to 0.

Offset 0x8: The rest of the packet is the encapsulated Ethernet packet

Figure 16.1. Ethernet data packet

17. GPIO interface

17.1. Connecting a user GPIO model

To register a GPIO user module, call `tsim_register_gpio_module(gpio_input, index)` from an input modules init function. Here `gpio_input` is a pointer to a `gpio_input` struct, and `index` is the index of the GPIO core to register on. See Chapter 5 for further details on how to connect the user model.

17.2. GPIO model API

The structure `struct gpio_input` models the GPIO pins. It is defined as:

```
/* GPIO input provider */
struct gpio_input {
    int index;
    int (*gpioout)(struct gpio_input *ctrl, unsigned int dir, unsigned int output);
    int (*gpioin) (struct gpio_input *ctrl, unsigned int in);
    void (*gpioinit)(struct gpio_input *ctrl);
    void (*gpioreset)(struct gpio_input *ctrl);
    void (*print_status)(struct gpio_input *ctrl);

    void* priv;
};
```

The `gpioout` callback should be set by the user module at startup. The `gpioin` callback is set by `tsim`. The `gpioout` callback is called by the module whenever a GPIO output pin changes. The `gpioin` callback is called by the user module when the input pins should change. Typically the user module would register an event handler at a certain time offset and call `gpioin` from within the event handler. The `gpioinit` callback is called during simulator startup and the `gpioreset` is called each time TSIM resets. Optionally the `print_status` callback can be set to print user model status. The `priv` parameter can be set freely by the user.

Table 17.1. *gpioout* callback parameters

Parameter	Description
<code>dir</code>	Bit <code>x</code> of <code>dir</code> indicates that the <code>grgpio</code> core drives output on line <code>x</code> when 1 and that it does not when it is 0.
<code>out</code>	The values of the output pins

Table 17.2. *gpioin* callback parameters

Parameter	Description
<code>in</code>	The input pin values

The return value of `gpioin/gpioout` is ignored.

See the `examples/input` directory for an example module implementation. See the `examples/test` directory for an example test program.

17.3. Commands

GPIO Commands

gpioX_status

Print status for the GPIO core.

gpioX_dbg [*flag*][*all*][*clean*][*list*]

Toggle specific flag, set all, clear all, or list debug flags for the given GPIO core. See Section 17.4 for a list of debug flags.

`X` in the above commands is the index of the core.

17.4. Debug flags

The following debug flags and debug subcommands are available for GPIO interfaces. The `GAISLER_GPIO_*` flags can be used with the **gpioX_dbg** command to toggle individual flags for individual GPIO cores and with the

dbgon command to toggle individual flags for all GPIO cores. The subcommands can be used with the **gpioX_dbg** command to change and list the settings of all flags for individual GPIO cores.

Table 17.3. GPIO debug flags

Flag/subcommand	Trace
GAISLER_GPIO_ACC	GPIO register accesses
GAISLER_GPIO_IRQ	GPIO interrupts
all	Set all GPIO debug flags for the core
clean	Set none of the GPIO debug flags for the core
list	List the current setting of the debug flags for the core

18. GRPCI, PCI initiator/target interface

TSIM models the GRPCI cores available in UT699, UT699E and UT700. For core details and register specification please see the manual for each chip.

18.1. Commands

PCI Commands

grpciX_status

Print status for PCI core X

grpciX_dbg

Toggle specific flag, set all, clear all, or list debug flags for the given grpci core. See Section 18.2 for a list of debug flags.

X in the above commands is the index of the core.

18.2. Debug flags

The following debug flags are available for the PCI interface. Use them in conjunction with the **grpciX_dbg** command to enable different levels of debug information.

Table 18.1. PCI interface debug flags

Flag	Trace
GAISLER_GRPCI_ACC	AHB accesses to/from PCI core
GAISLER_GRPCI_REGACC	GRPCI APB register accesses
GAISLER_GRPCI_DMA_REGACC	PCIDMA APB register accesses
GAISLER_GRPCI_DMA	GRPCI DMA accesses on the AHB bus
GAISLER_GRPCI_TARGET_ACC	GRPCI target accesses
GAISLER_GRPCI_INIT	Print summary on startup

18.3. PCI bus model API

To register a GRPCI module call `tsim_register_grpci_module(struct grpci_input *inp, int index);` from an input modules init function. Here *inp* is a pointer to a `grpci_input` struct and *index* is the index of the GRPCI controller to register on. See Chapter 5 for further details on how to connect the user model. The struct `grpci_input` is defined in `grpci_input.h` as:

```
struct grpci_input {
    int (*acc)(struct grpci_input *ctrl,
              int cmd,
              unsigned int addr,
              unsigned int wsize,
              unsigned int *data,
              unsigned int *abort,
              unsigned int *ws);

    void (*grpci_init)(struct grpci_interface *grpciif);
};
```

The `acc` callback should be set by the PCI user module at startup. It is called by the the model whenever the PCI core reads/writes as a PCI bus master.

Table 18.2. acc callback parameters

Parameter	Description
cmd	Command to execute, see Section 18.3.1 details.
addr	PCI address.

Parameter	Description
wsiz	0: 8-bit access 1: 16-bit access, 2: 32-bit access. Is always 2 for read accesses.
data	Data buffer. The user module should return the read data in <i>*data</i> for read commands or write the data in <i>*data</i> for write commands.
abort	Set <i>*abort</i> to 1 to generate target abort, or 0 otherwise.
ws	Set <i>*ws</i> to the number of PCI clocks it takes to complete the transaction.

The return value of `acc` determines if the transaction terminates successfully (0 or `GRPCI_ACC_OK`) or with master abort (1 or `GRPCI_ACC_MASTER_ABORT`).

The `grpci_init` callback should be set by the PCI user module at startup. It is called by TSIM at simulator startup.

Table 18.3. *grpci_init* callback parameters

Parameter	Description
grpciif	Pointer to a <code>struct grpci_interface</code> . Should be saved by the module to interface with TSIM's GRPCI model.

The `struct grpci_interface` is defined in `grpci_input.h` as:

```
struct grpci_interface {
    int (*target_acc)(int index,
                     int cmd,
                     unsigned int addr,
                     unsigned int wsiz,
                     unsigned int *data,
                     unsigned int *mexc);
};
```

The callback `target_acc` is installed by the TSIM. The PCI user dynamic library can call this function to initiate an access to the PCI target.

Table 18.4. *target_acc* parameters

Parameter	Description
index	Index of GRPCI core of the system. Typically, 0 is the only valid index.
cmd	Command to execute, see Section 18.3.1 for details. I/O cycles are not supported by the target.
addr	PCI address. Should always be word aligned for read accesses.
wsiz	0: 8-bit access 1: 16-bit access, 2: 32-bit access. Should always be 2 for read accesses.
data	Data buffer. The read data is returned in <i>*data</i> for read commands or the data in <i>*data</i> is written for write commands.
mexc	The model sets <i>*mexc</i> to 0 if access is successful, or 1 in case of target abort.

If a supported command hits `MEMBAR0`, `MEMBAR1` or `CONFIG`, `target_acc()` will return 0. For unsupported commands or other areas, it will return 1.

18.3.1. PCI command table

Table 18.5. *PCI command table*

Command	Description
0	IRQ acknowledge
1	Special cycle
2	I/O Read

Command	Description
3	I/O Write
4	Reserved
5	Reserved
6	Memory Read
7	Memory Write
8	Reserved
9	Reserved
10	Configuration Read
11	Configuration Write
12	Memory Read Multiple
13	Dual Address Cycle
14	Memory Read Line
15	Memory Write And Invalidate

18.4. Examples

See the PCI files in `examples/input` for header files and an example PCI user module. See example usage in `examples/test`.

19. GRSPW1, SpaceWire interface with RMAP support

The UT699 chip contains 4 GRSPW cores which are modelled in TSIM. For core details and register specification please see the UT699 manual.

The UT699E chip has GRSPW2 cores instead of GRSPW cores. So, for UT699E see Chapter 20 instead.

The following features are supported:

- Transmission and reception of SpaceWire packets
- Interrupts
- RMAP

19.1. Start up options

SpaceWire core start up options

- grspwX_connect host:port
Connect GRSPW core X to packet server at specified server and port.
- grspwX_server port
Open a packet server for core X on specified port.
- grspw_rxfreq freq
Set the RX frequency which is used to calculate receive performance.
- grspw_txfreq freq
Set the TX frequency which is used to calculate transmission performance.

X in the above commands is the index of the core.

19.2. Commands

GRSPW SpaceWire core TSIM commands

- grspwX_connect** host:[port]
Connect GRSPW core X to packet server at specified server and TCP port.
- grspwX_server** port
Open a packet server for GRSPW core X on specified TCP port.
- grspwX_dbg** [flag|all|clean|list]
Toggle specific flag, set all, clear all, or list debug flags for the given GRSPW core. See Section 19.3 for a list of debug flags.

X in the above commands is the index of the core.

19.3. Debug flags

The following debug flags are available for the SpaceWire interfaces. Use the them in conjunction with the **dbgon** command to enable different levels of debug information.

Table 19.1. SpaceWire debug flags

Flag	Trace
GAISLER_GRSPW_ACC	GRSPW accesses
GAISLER_GRSPW_RXPACKET	GRSPW received packets
GAISLER_GRSPW_RXCTRL	GRSPW rx protocol
GAISLER_GRSPW_TXPACKET	GRSPW transmitted packets
GAISLER_GRSPW_TXCTRL	GRSPW tx protocol

19.4. SpaceWire packet server

Each SpaceWire core can be configured independently as a packet server or client using either -grspwX_server or -grspwX_connect. TCP sockets are used for establishing the connections. When acting as a server the core can only accept a single connection.

A connection should be set up before starting simulation for the first time, and must not be broken after that. Restarting the simulation will not tear down the connection, nor emptying any socket buffers. The socket based interface does not support any signalling of restart of the simulation. To ensure a clean restart of simulation when using this interface, restarting TSIM entirely and reconnecting socket interfaces is advisable.

For more flexibility, such as custom routing, an external packet server can be implemented using the protocol specified in the following sections. Each core should then be connected to that server.

19.5. SpaceWire packet server protocol

The protocol used to communicate with the packet server is described below. Three different types of packets are defined according to the table below.

Table 19.2. Packet types

Type	Value
Data	0
Time code	1

Note that all packets are prepended by a one word length field which specified the length of the coming packet including the header.

19.5.1. Data packet format

Packet length at offset 0x0:

31 0

LEN

31:0 LEN Length of rest of packet: 4 + number of data bytes

Header at offset 0x4:

31 16 15 8 7 5 4 1 0

R	IPID	TYPE	R	EE
---	------	------	---	----

31:16 R Reserved for future use. Must be set to 0.

15:8 IPID IP core ID: 0 for SpaceWire

7:5 TYPE Packet type: 0 for data packets

4:1 R Reserved for future use. Must be set to 0.

0 EE Error End of Packet. Set when the packet is truncated and terminated by an EEP.

Offset 0x8: The rest of the packet is the encapsulated SpaceWire packet

Figure 19.1. SpaceWire data packet

19.5.2. Time code packet format

Packet length at offset 0x0:

31 0

LEN																																		
-----	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

31:0 LEN Length of rest of packet: 8

Header at offset 0x4:

31 16 15 8 7 5 4 0

R																IPID								TYPE				R							
---	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	------	--	--	--	--	--	--	--	------	--	--	--	---	--	--	--	--	--	--	--

31:16 R Reserved for future use. Must be set to 0.

15:8 IPID IP core ID: 0 for SpaceWire

7:5 TYPE Packet type: 1 for time code packets

4:0 R Reserved for future use. Must be set to 0.

Payload at offset 0x8:

31 8 7 6 5 0

R																								CT				CN							
---	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	----	--	--	--	----	--	--	--	--	--	--	--

31:8 R Reserved for future use. Must be set to 0.

7:6 CT Time control flags

5:0 CN Value of time counter

Figure 19.2. SpaceWire time code packet

20. GRSPW2, SpaceWire interface with RMAP support

TSIM models the GRSPW2 cores available in UT699E, UT700, GR712RC and GR716. For core details and register specification please see the manual for each chip.

Supported features include:

- Transmission and reception of SpaceWire packets
- Transmission and reception of Time codes
- RMAP
- Server side link state model
- Link errors
- Link error injection

All GRSPW2 register fields with underlying functionality in UT699E, UT700, GR712RC and GR716 are supported except for:

- The link model is only in error reset state or run state.
- The RMAP buffer disable (RD) bit in the control register with underlying functionality is not modelled.
- The limitations of the No spill (NS) DMA control register bit as noted in the section on Flow control limitations below.
- No support for RX/TX of SpW interrupt codes (GR716).
- No support for SpaceWire Plug & Play via RMAP access (GR716).
- The port loopback (Loop) bit in the control register with underlying functionality is not modelled (UT700).

20.1. Start up options

SpaceWire core start up options

- grspwX_connect host:port
Connect GRSPW2 core X to packet server at specified server and port.
- grspwX_server port
Open a packet server for core X on specified port.
- grspw_spwfreq freq
Sets the SpaceWire input clock frequency. Combined with the clock divisor register, this determines the startup frequency and TX frequency.
- grspw_clkdiv value
Sets the reset value for the clock divisor register for all GRSPW2 cores.
- grspw_tx_max_part_len len
Sets up all GRSPW2 cores to transmit any SpaceWire packet longer than len in data part packets with no more than len bytes of data.
- grspw_endpacket [0|1]
Enable (or disable with 0 argument) end marking data part packets. When enabled, the last data part packet of a simulated SpaceWire packet will always be a data part packet with no data and an end marker. This is the default unless simple mode is enabled. When disabled the last data part packet can contain both data and an end marker. This is the default when simple mode is enabled.
- grspw_simple [0|1]
Enable "simple mode" for all GRSPW2 cores. This can be used for backward compatibility with TSIM 2.0.44 and backwards. See the separate section on simple mode for details.
- grspw_simple_rxfreq freq
Sets the RX frequency in MHz for all GRSPW2 cores to freq. This is only valid together with the -grspw_simple option.

X in the above commands is the index of the core.

20.2. Commands

GRSPW2 SpaceWire core TSIM commands

- grspwX_connect host:[port]**
Connect GRSPW2 core X to packet server at specified server and TCP port.

grspwX_server port

Open a packet server for GRSPW2 core X on specified TCP port.

grspwX_dbg [flag|all|clean|list]

Toggle specific flag, set all, clear all, or list debug flags for the given GRSPW2 core. See Section 20.3 for a list of debug flags.

grspwX_status

Print status for GRSPW2 core X.

X in the above commands is the index of the core.

20.3. Debug flags

The following debug flags and debug subcommands are available for SpaceWire interfaces. The *GAISLER_GRSPW_** flags can be used with the **grspwX_dbg** command to toggle individual flags for individual SpaceWire cores and with the **dbgon** command to toggle individual flags for all GRSPW2 cores. The subcommands can be used with the **grspwX_dbg** command to change and list the settings of all flags for individual SpaceWire cores.

Table 20.1. SpaceWire debug flags

Flag/subcommand	Trace
GAISLER_GRSPW_ACC	GRSPW accesses
GAISLER_GRSPW_RXPACKET	GRSPW received packets
GAISLER_GRSPW_RXCTRL	GRSPW rx protocol
GAISLER_GRSPW_TXPACKET	GRSPW transmitted packets
GAISLER_GRSPW_TXCTRL	GRSPW tx protocol
GAISLER_GRSPW_RMAP	GRSPW RMAP accesses
GAISLER_GRSPW_RMAPPACKET	GRSPW RMAP packet dumps
GAISLER_GRSPW_RMAPPACKDE	GRSPW RMAP packet decoding
GAISLER_GRSPW_DMAERR	GRSPW DMA errors
GAISLER_GRSPW_LINK	Link changes
GAISLER_GRSPW_PART	TX/RX of GRSPW data part packets
all	Set all debug flags for the core
clean	Set none of the debug flags for the core
list	List the current setting of the debug flags for the core

20.4. SpaceWire packet server

Each SpaceWire core can be configured independently as a packet server or client using either **-grspwX_server** or **-grspwX_connect**. TCP sockets are used for establishing the connections. When acting as a server the core can only accept a single connection.

A connection should be set up before starting simulation for the first time, and must not be broken after that. Restarting the simulation will not tear down the connection, nor emptying any socket buffers. The socket based interface does not support any signalling of restart of the simulation. To ensure a clean restart of simulation when using this interface, restarting TSIM entirely and reconnecting socket interfaces is advisable.

The server side contains a link model that gets control information from the models at each end of the link, determines the link state and communicates frequencies and link errors to the two models at each ends of the link. It also supports error injection via two error injection packet types that can be sent from a custom client. See the following sections for details.

For more flexibility, such as custom routing, an external packet server can be implemented using the protocol specified in the following sections. Each core should then be connected to that server. That server would also

have to implement a link model that at least reacts to link control packets and sends out link state packets and RX frequency packets.

20.5. SpaceWire packet server protocol

The protocol used to communicate with the packet server is described below. The different types of packets are defined according to the table below.

Table 20.2. Packet types

Type	Value	Direction	Notes
Data part	0	Both	Only when in run state
Time code	1	Both	Only when in run state
Link state	2	Server to client	
Link control	3	Client to server	Must be sent for model to reach run state
RX frequency	4	Server to client	
Error injection	5	Client to server	Optional
Packet error request	6	Client to server	Optional

All packets begin with a 32-bit big endian word length field which specifies the length of the rest of the packet, including header and other fixed fields. For most packet types this length is fixed for the particular type. Apart from the data part packet type, where data follows the header byte-wise, all fields are 32-bit big endian words if not otherwise specified.

All packets received by the GRSPW2 model are handled sequentially, and all packets sent by the GRSPW2 model and the server side link model are supposed to be handled sequentially by the client. SpaceWire packets can be split into multiple data parts, transferred in data part packets. Between such parts other packets such as for time codes, link state changes, link control changes, etc., can be handled. During the simulated time span for the reception of a data part, the receiver will not/should not handle any other packet types. Use the `-grspw_tx_max_part_len` option to set up GRSPW2 model to split up SpaceWire packets into data parts in order for such events to be able to happen during the data stream.

20.5.1. Flow control limitations

Flow control in terms of credit is not modelled between two ends of a link. A transmitter gets no notice if the other end cannot give more credit. If the no-spill bit in the GRSPW2 core is set and an enabled receiving DMA channel has no enabled descriptors, the data part packet will be held on the receiving side until a descriptor is available. Due to the sequential nature of the packet model a link error, time code, etc. will not be handled at all by the GRSPW2 model during this time.

20.5.2. Data part packet format


A SpaceWire packet is represented by one or more data parts. A data part packet represents one such a part. For the data parts of a multi part SpaceWire packet, only the last data part should have an EOP or EEP end marker, i.e. the `END` field set to 0 or 1. The other parts should have no end marker, i.e. the `END` field set to 2. Each data part is delivered in its entirety or not at all. A link error occurring between data parts on the other hand cuts the SpaceWire packet short and is considered the end of that SpaceWire packet.

A data part packet is sent at the beginning of transmission of the corresponding part of the SpaceWire packet, so that the receiver can start reacting to it as soon as the transmission starts. The GRSPW2 model by default sends a SpaceWire packet in the form of two data part packets. The first data part packet is sent at the beginning of transmission and contains all data but has no end marker. The second data part packet is sent when transmission is completed and has the appropriate end marker set but contains no data. If a user model is not waiting for the end marker packet before responding, the response could arrive before transmission is considered done by the GRSPW2 model. Generation of separate end marker packets can be turned off using the `-grspw_endpacket`

20.5.4. Link state packet format


Link state packets are sent out by the server side link model when the link state changes. The only states currently simulated are `Error Reset` and `Run`. A link state packet with state `Error Reset` can have the `ERROR` field set to an error seen at the receiver. Other link state packets has only `None` in the `ERROR` field.

Packet length at offset 0x0:



31:0 LEN Length of rest of packet: 4

Header at offset 0x4:



- 31:19 R Reserved for future use. Must be set to 0.
- 18:16 ERROR Link error: 0: None, 1: Disconnect, 2: Parity, 3: Escape, 4:Credit
- 15:8 IPID IP core ID: 0 for SpaceWire
- 7:5 TYPE Packet type: 2 for link state packets
- 4:3 R Reserved for future use. Must be set to 0.
- 2:0 LS Link State: 0: Error reset, 1: Error wait, 2: Ready, 3: Started, 4: Connecting, 5: Run

Figure 20.3. SpaceWire link state packet

20.5.5. Link control packet format

A link control packet must be sent from a client to the server side link model to inform if that side of the link is in start mode, autostart mode, and/or has the link disabled. In addition, the control packet contains information on the startup frequency and the TX frequency that will be used once run state is reached. A new link control packet should be sent from a client any time any of these parameters change.

If the startup frequencies of the two ends differ by more than a factor 1.1/0.9, the link model will reach run state. This limit is chosen based on the limits on timeout periods in the SpaceWire standard that must be within 10% up or down from nominal frequency. So even though the startup frequency should be 10 MHz, run state can be reached if startup frequencies are close enough.

Packet length at offset 0x0:

31 0

LEN	
-----	--

31:0 LEN Length of rest of packet: 8

Header at offset 0x4:

31 16 15 8 7 5 4 0

R	IPID	TYPE	R
---	------	------	---

31:16 R Reserved for future use. Must be set to 0.

15:8 IPID IP core ID: 0 for SpaceWire

7:5 TYPE Packet type: 4 for rx frequency packets

4:0 R Reserved for future use. Must be set to 0.

RX frequency in MHz at offset 0x8:

31 0

RFREQ	
-------	--

31:0 RFREQ RX frequency in MHz, big endian IEEE-754 32-bit float

Figure 20.5. SpaceWire rx frequency packet

20.5.7. Link error injection packet format

A client can send a packet of this kind to the server side link model to request that a link error will occur. The error specified is the link error that is seen at the targeted end. The *OE* bit determines which end of the link is the targeted end, i.e. will see the error.

If the *OE* bit is set to 1, the error will be seen at the receiver of the simulation model on the other end. The simulation model on the client side will see a disconnect error via a link state packet. In order for this error to happen during reception of a SpaceWire packet at the other end, the client can send a data part packet with no end marker followed by a link error injection packet.

If the *OE* bit is set to 0, the error will be seen at the receiver on the client end. The simulation model at the client end will see the requested error via a link state packet. The simulation model at the other end will see a disconnect error. Note that due to the nature of the model, this cannot in general be relied upon to inject an error during the reception of a SpaceWire packet, even if split up in multiple data parts. The link state packet will not be sent by the server side link model until all previous packets have been handled, and the client should handle all other packets queued up before that link state packet can be handled. To inject a link error during the reception of a SpaceWire packet at the client side, the packet error request packet should be used instead.

Packet length at offset 0x0:

31 0

LEN	
-----	--

31:0 LEN Length of rest of packet: 4

Header at offset 0x4:

31 21 20 19 18 16 15 8 7 5 4 0

R	OE	R	ERROR	IPID	TYPE	R
---	----	---	-------	------	------	---

31:21 R Reserved for future use. Must be set to 0.
 20 OE Other end: 1: other end gets the error, 0: my end gets error
 19 R Reserved for future use. Must be set to 0.
 18:16 ERROR Link error: 1: Disconnect, 2: Parity, 3: Escape, 4:Credit
 15:8 IPID IP core ID: 0 for SpaceWire
 7:5 TYPE Packet type: 5 for link error injection packets
 4:0 R Reserved for future use. Must be set to 0.

Figure 20.6. SpaceWire link error injection packet

20.5.8. Packet error request packet format

A client can send a packet of this kind to the server side link model to request that a link error will occur during reception of a certain data packet by the client. The error specified is the link error that is seen, via a link state packet, by the client as a result. The other side will see a disconnect error. A 64-bit packet number, counting from 0, indicates during which SpaceWire packet sent from the other side to the client the link error should happen. Note that this number is indexing SpaceWire packets, not individual data part packets, and does not take SpaceWire packets sent from the client to the server side into account in the numbering. There can only be one outstanding packet error request per targeted GRSPW2 core at a time.

The **grspwX_status** command can be issued for the targeted GRSPW2 core to see how many SpaceWire packets have currently been sent by that core. This includes started but aborted SpaceWire packets, due to link error, core reset or active aborting using the Abort TX (AT) bit in the DMA control register of the GRSPW2 core.

Packet length at offset 0x0:

31 0

LEN	
-----	--

31:0 LEN Length of rest of packet: 16

Header at offset 0x4:

31 19 18 16 15 8 7 5 4 0

R	ERROR	IPID	TYPE	R
---	-------	------	------	---

31:19 R Reserved for future use. Must be set to 0.

18:16 ERROR Link error: 1: Disconnect, 2: Parity, 3: Escape, 4:Credit

15:8 IPID IP core ID: 0 for SpaceWire

7:5 TYPE Packet type: 6 for packet error request packets

4:0 R Reserved for future use. Must be set to 0.

Packet number to request error for, most significant word at offset 0x8:

31 0

MSW	
-----	--

31:0 MSW Bits 63:32 of unsigned 64-bit big endian integer

Packet number to request error for, least significant word at offset 0xc:

31 0

LSW	
-----	--

31:0 LSW Bits 31:0 of unsigned 64-bit big endian integer

Reserved field at offset 0x10:

31 0

R	
---	--

31:0 R Reserved for future use. Must be set to 0.

Figure 20.7. SpaceWire packet error request packet

20.6. Simple Mode

For backwards compatibility with TSIM 2.0.44 and older, the GRSPW2 models can be set up in “simple mode” with the `-grspw_simple` option. This makes the following changes to the simulation model for all GRSPW2 cores:

- The *only* supported packet types are data part packets and time code packets. The model sends out no other packet types and accepts no other packet types.
- In simple mode a SpaceWire packet is by default sent as a single data part packet *with* an end marker. Generation of separate end packets can be enabled with the `-grspw_endpacket` option. Simple mode *does* support all kinds of data part packets. However, if one needs to be compatible with the older protocol, each data part packet should contain a full SpaceWire packet with an end marker and the `-grspw_tx_max_part_len` option should not be used.
- The link state that a GRSPW2 core perceives is solely determined by its own link control setting. The other end is assumed to try to start the link. In other words, run state is achieved once the GRSPW2 is set to start or

autostart without having link disable set. Moreover, startup frequencies are ignored and run state is achieved without any delay.

- The RX frequency is determined primarily by the `-grspw_simple_rxfreq` option. If that is not used, the RX frequency is taken by the `-grspw_spwfreq` option. If none of those options are set the CPU frequency is used. No cases take any clock divisors into account. The TX frequency is determined in the usual way as when not in simple mode, which includes taking the clock divisor register into account.

21. SPI interface

21.1. Connecting a user SPI model

To register a SPI user module, call `tsim_register_spi_module(spi_input, index)` from an input modules init function. Here `spi_input` is a pointer to a `spi_input` struct, and `index` is the index of the SPI core to register on. See Chapter 5 for further details on how to connect the user model.

21.2. SPI bus model API

The structure `struct spi_input` models the SPI bus. It is defined as:

```
/* Spi input provider */
struct spi_input {
    int (*spishift)(struct spi_input *ctrl, uint32 select, uint32 bitcnt,
                   uint32 out, uint32 *in);
    void *priv;
};
```

The `spishift` callback should be set by the SPI user module at startup. It is called by the SPI core whenever it shifts a word through the SPI bus.

Table 21.1. *spishift callback parameters*

Parameter	Description
select	Slave select bits
bitcnt	Number of bits set in the MODE register, if bitcnt is -1 then the operation is not a shift and the call is to indicate a <i>select</i> change, i.e. if the core is disabled.
out	Shift out (tx) data
in	Shift in (rx) data

The `priv` parameter is a pointer to private data and be set freely by the user.

The return value of `spishift` is ignored.

See the `examples/input` directory for an example module implementation. See the `examples/test` directory for an example test program.

21.3. Commands

SPI Commands

spiX_dbg [*flag*][*all*][*clean*][*list*]

Toggle specific flag, set all, clear all, or list debug flags for the given SPI core. See Section 21.4 for a list of debug flags.

21.4. Debug flags

The following debug flags and debug subcommands are available for SPI interfaces. The `GAISLER_SPI_*` flags can be used with the **spiX_dbg** command to toggle individual flags for individual SPI cores and with the **dbgon** command to toggle individual flags for all SPI cores. The subcommands can be used with the **spiX_dbg** command to change and list the settings of all flags for individual SPI cores.

Table 21.2. *SPI debug flags*

Flag/subcommand	Trace
GAISLER_SPI_ACC	SPI register accesses
GAISLER_SPI_IRQ	SPI interrupts

Flag/subcommand	Trace
all	Set all SPI debug flags for the core
clean	Set none of the SPI debug flags for the core
list	List the current setting of the debug flags for the core

22. SPIM interface

22.1. Connecting a user SPIM model to TSIM

To register a user module on a SPIM controller call `tsim_register_spim_module(spim_subsystem, index)` from an input modules init function. Here `spim_subsystem` is a pointer to a `spim_subsystem` struct and `index` is the index of the SPIM controller to register on. See Chapter 5 for further details on how to connect the user model. The struct `spim_subsystem` is defined in `spim_input.h` as:

```
struct spim_subsystem {
    struct spim_input *inp;
};
```

22.2. SPIM model API

The structure `struct spim_input` models the SPIM bus. It is defined as:

```
/* Spim input provider */

struct spim_input {
    int (*spishift)(struct spim_input * ctrl, unsigned int select,
                    unsigned int bitcnt, unsigned int timing_scaler,
                    unsigned int out, unsigned int *in);
    void (*spim_init)(struct spim_interface *spimif);
    void *priv;
};
```

The `spishift` callback should be set by the SPIM user module at startup. It is called by TSIM3 whenever a new byte is written to the TX register.

Table 22.1. *spishift callback parameters*

Parameter	Description
select	Slave select bits
bitcnt	Number of bits the user model will receive. This will always be set to 8.
timing_scaler	The relation between the SPIM core SCK and the system clk.
out	Shift out (tx) data
in	Shift in (rx) data

The `priv` is a pointer to private data and can be set freely by the user. The `spim_init` is called at startup and provides the user model with a SPIM interface struct. The SPIM interface struct is defined as:

```
struct spim_interface {
    int (*spim_get_flashb)(unsigned int index, void *data);
};
```

Table 22.2. *spim_get_flashb parameters*

Parameter	Description
index	Index of the SPIM controller to access.
data	Pointer to a <code>spim_flash_data</code> struct to be filled in.

The `spimif` struct allows access to TSIM3s internal SPIM memory representation with `spim_get_flashb`. `index` is the index of the SPIM controller to access. The `data` parameter should be a pointer to a `spim_flash_data` struct which will be updated with the necessary data to access the internal memory representation. The `spim_flash_data` struct is defined as:

```
struct spim_flash_data {
    unsigned int flash_size;
    unsigned char *flashb;
    unsigned int flash_mask;
};
```

Table 22.3. struct spim_flash_data members

Parameter	Description
flash_size	Size of the flash memory.
flashb	Pointer to the flash memory.
flash_mask	Flash memory mask.

See the `examples/input` directory for an example module implementation. The example demonstrates how to set up a basic model, get access to TSIM's internal memory representation and updates the RX register. See the `examples/test` directory for an example test program.

23. AT697 PCI interface

TSIM models the PCI interface in AT697, in TSIM called “ESAPCI”. For core details and register specification please see the manual for the chip.

The PCI model will process all accesses to memory region 0xa0000000 - 0xf0000000 (AHB slave mode) and the APB registers starting at 0x80000100. The AT697 PCI model implements all registers of the PCI core. It will in turn load the PCI user modules that will implement the devices. The AT697 model is supposed to be the PCI host. Both PCI Initiator mode and PCI Target mode are supported. The interface to the PCI user modules is implemented on bus level. Two callbacks model the PCI bus.

23.1. Commands

ESAPCI TSIM Commands

esapci0_dbg

Toggle specific flag, set all, clear all, or list debug flags for the given PCI core. See Section 23.2 for a list of debug flags.

23.2. Debug flags

The following debug flags are available for the ESAPCI interface. Use them in conjunction with the **esapci0_dbg** command to enable different levels of debug information.

Table 23.1. ESAPCI interface debug flags

ESAPCI_REGACC	Trace accesses to the PCI registers
ESAPCI_ACC	Trace accesses to the PCI AHB-slave address space
ESAPCI_DMA	Trace DMA
ESAPCI_IRQ	Trace PCI IRQ

23.3. Registers

Table 23.2 contains a list of implemented and not implemented fields of the AT697F PCI Registers. Only register fields that are relevant for the emulated PCI module is implemented.

Table 23.2. PCI register support

Register	Implemented	Not implemented
PCIID1	device id, vendor id	
PCISC	stat 13, stat 12, stat 11, stat 7, stat 6 stat 5, stat 4, com2, com 1, com1	stat15 stat14 stat10_9 stat8 com10 com9 com8 com7 com6 com5 com4 com3
PCIID2	class code, revision id	
PCIBHDL	[bist, header type, latency timer, cache size] config-space only	
PCIMBAR1	base address, pref, type, msi	
PCIMBAR2	base address, pref, type, msi	
PCIIOBAR3	io base address, ms	
PCISID	subsystem id, svi	
PCICP	pointer	
PCILI	[max_lat min_gnt int_pin int_line] config-space-only	
PCIRT	[retry trdy] config-space-only	
PCICW		ben

Register	Implemented	Not implemented
PCISA	start address	
PCIW		ben
PCIDMA	wdcnt, com	b2b
PCIIS	act, xff, xfe, rfe	dmas, ss
PCIIC	mod, commsb	dwr, dww, perr
PCITPA	tpa1, tpa2	
PCITSC		errmem, xff, xfe, rfe, tms
PCIITE	dmaer, imier, tier	cmfer, imper, tbeer, tper, syser
PCIITP	dmaer, imier, tier	cmfer, imper, tbeer, tper, syser
PCIITF	dmaer, imier, tier, cmfer, imper, tbeer, tper, syser	
PCID	dat	
PCIBE	dat	
PCIDMAA	addr	
PCIA		p0, p1, p2, p3

23.4. ESAPCI bus model API

To register a ESAPCI module call `tsim_register_esa_pci_module(struct esa_pci_input *inp, int index);` from an input modules init function. Here *inp* is a pointer to a `esa_pci_input` struct and *index* is the index of the ESAPCI controller to register on. See Chapter 5 for further details on how to connect the user model. The struct `esa_pci_input` is defined in `esa_pci_input.h` as:

```
struct esa_pci_input {
    int (*acc)(struct esa_pci_input *ctrl,
               int cmd,
               unsigned int addr,
               unsigned int wsize,
               unsigned int *data,
               unsigned int *abort,
               unsigned int *ws);

    void (*esapci_init)(struct esa_pci_interface *esapciif);
};
```

The `acc` callback should be set by the PCI user module at startup. It is called by the the model whenever the PCI core reads/writes as a PCI bus master.

Table 23.3. *acc* callback parameters

Parameter	Description
cmd	Command to execute, see Section 23.4.1 details.
addr	PCI address.
wsize	0: 8-bit access 1: 16-bit access, 2: 32-bit access. Is always 2 for read accesses.
data	Data buffer. The user module should return the read data in <i>*data</i> for read commands or write the data in <i>*data</i> for write commands.
abort	Set <i>*abort</i> to 1 to generate target abort, or 0 otherwise.
ws	Set <i>*ws</i> to the number of PCI clocks it takes to complete the transaction.

The return value of `acc` determines if the transaction terminates successfully (0 or `ESA_PCI_ACC_OK`) or with master abort (1 or `ESA_PCI_ACC_MASTER_ABORT`).

The `esapci_init` callback should be set by the PCI user module at startup. It is called by TSIM at simulator startup.

Table 23.4. *esapci_init* callback parameters

Parameter	Description
esapciif	Pointer to a struct <code>esa_pci_interface</code> . Should be saved by the module to interface with TSIM's ESAPCI model.

The struct `esa_pci_interface` is defined in `esapci_input.h` as:

```
struct esa_pci_interface {
    int (*target_acc)(int index,
                     int cmd,
                     unsigned int addr,
                     unsigned int wsize,
                     unsigned int *data,
                     unsigned int *mexc);
};
```

The callback `target_acc` is installed by the TSIM. The PCI user dynamic library can call this function to initiate an access to the PCI target.

Table 23.5. *target_acc* parameters

Parameter	Description
index	Index of ESAPCI core of the system. This should be 0.
cmd	Command to execute, see Section 23.4.1 for details. Configuration cycles are not supported. ESAPCI is supposed to be the host.
addr	PCI address. Should always be word aligned for read accesses.
wsize	0: 8-bit access 1: 16-bit access, 2: 32-bit access. Should always be 2 for read accesses.
data	Data buffer. The read data is returned in <code>*data</code> for read commands or the data in <code>*data</code> is written for write commands.
mexc	The model sets <code>*mexc</code> to 0 if access is successful, or 1 in case of target abort.

If a supported command hits MEMBAR0, MEMBAR1 or IOBAR, `target_acc()` will return 0. For unsupported commands or other areas, it will return 1.

23.4.1. PCI command table

Table 23.6. *PCI command table*

Command	Description
0	IRQ acknowledge
1	Special cycle
2	I/O Read
3	I/O Write
4	Reserved
5	Reserved
6	Memory Read
7	Memory Write
8	Reserved
9	Reserved
10	Configuration Read
11	Configuration Write
12	Memory Read Multiple

Command	Description
13	Dual Address Cycle
14	Memory Read Line
15	Memory Write And Invalidate

23.5. Examples

See the PCI files in `examples/input` for header files and an example PCI user module. See example usage in `examples/test`.

24. TPS VxWorks 6.x AHB Module

24.1. Overview

The TPS VxWorks Module is a loadable module that simplifies communication between TSIM and the VxWorks Workbench for VxWorks 6.7 and 6.9. It provides a virtual core that acts similar to a basic Ethernet controller, but does not require a packet server.

The module is only useful in conjunction with VxWorks 6.7 and 6.9. See also Section 5.3.4 on some limitations of some features when using this module.

Table 24.1. Files delivered with the TPS VxWorks TSIM module

File	Description
tps/linux/tps-vxworks.so	TPS VxWorks module for Linux
tps/win64/tps-vxworks.dll	TPS VxWorks module for Windows

24.2. Loading the module

The module is loaded using the TSIM3 option `-mod`. It can be used in conjunction with other modules, such as the UT699 and GR712RC modules.

On Linux (together with the UT699 design):

```
tsim-leon3 -ut699 -mod ./tps/linux/tps-vxworks.so
```

On Windows (together with the GR712RC design):

```
tsim-leon3 -gr712rc -mod ./tps/win64/tps-vxworks.dll
```

24.3. Configuration

By default the module uses IRQ 5 and UDP port 0x4321. This can be changed by using the following command line arguments:

- tps_vxworks_irq irq**
Uses IRQ `irq` instead of the default.
- tps_vxworks_port port**
Uses UDP port `port` instead of the default.

Use the following command line to make the TPS module use IRQ 10 and port 5000 on Linux together with the UT699 design:

```
tsim-leon3 -ut699 -mod ./tps/linux/tps-vxworks.so
            -tps_vxworks_port 5000 -tps_vxworks_irq 10
```

25. Support

For support contact the Cobham Gaisler support team at support@gaisler.com.

When contacting support, please identify yourself in full, including company affiliation and site name and address. Please identify exactly what product that is used, specifying if it is an IP core (with full name of the library distribution archive file), component, software version, compiler version, operating system version, debug tool version, simulator tool version, board version, etc.

The support service is only for paying customers with a support contract.

Cobham Gaisler AB
Kungsgatan 12
411 19 Gothenburg
Sweden
www.cobhamaes.com/gaisler
sales@gaisler.com
T: +46 31 7758650
F: +46 31 421407

Cobham Gaisler AB, reserves the right to make changes to any products and services described herein at any time without notice. Consult Cobham or an authorized sales representative to verify that the information in this document is current before using this product. Cobham does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by Cobham; nor does the purchase, lease, or use of a product or service from Cobham convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual rights of Cobham or of third parties. All information is provided as is. There is no warranty that it is correct or suitable for any purpose, neither implicit nor explicit.

Copyright © 2020 Cobham Gaisler AB